Prepared by:
Nate Vaillancourt
ADVANTAGE TRUCK GROUP
220 FRONTAGE RD.
MANCHESTER, NH 03103
Phone:

A proposal for **TOWN OF BARRINGTON**

Prepared by ADVANTAGE TRUCK GROUP Nate Vaillancourt

May 06, 2024

Western Star 47X



Components shown may not reflect all spec'd options and are not to scale

Prepared by:
Nate Vaillancourt
ADVANTAGE TRUCK GROUP
220 FRONTAGE RD.
MANCHESTER, NH 03103
Phone:

QUOTATION

WESTERN STAR 47X

SET FORWARD AXLE - TRUCK
CUM L9 330 HP @ 2200 RPM; 2200 GOV RPM, 1000 LBFT @ 1200 RPM
ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH
PTO PROVISION
CUMMINS-MERITOR RS-30-185 30,000# U-SERIES
SINGLE REAR AXLE

30,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD

CUMMINS-MERITOR MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE

9,500# LEFT, 10,500# RIGHT MIXER/PLOW FLAT LEAF FRONT SUSPENSION (20,000#) 111.6 INCH BBC CONVENTIONAL ALUMINUM CAB 4740MM (187 INCH) WHEELBASE, SFA ONLY 13.0MM X 87.0MM X 311.0MM STEEL FRAME (0.51X3.43X12.24 INCH) 120 KSI 1575MM (62 INCH) REAR FRAME OVERHANG

			PER UNIT	TOTAL
VEHICLE PRICE	TOTAL # OF UNITS (1)	\$	135,108	\$ 135,108
EXTENDED WARRANTY		\$	0	\$ 0
DEALER INSTALLED OPTIONS		\$	0	\$ 0
CUSTOMER PRICE BEFORE TAX		\$	135,108	\$ 135,108
TAXES AND FEES				
TAXES AND FEES		\$	0	\$ 0
OTHER CHARGES		\$	0	\$ 0
TRADE-IN				
TRADE-IN ALLOWANCE		\$	(0)	\$ (0)
BALANCE DUE COMMENTS:	(LOCAL CURRENCY)	\$	135,108	\$ 135,108
Projected delivery on/ / provided the	ne order is received before _	/	/	
APPROVAL:				
Please indicate your acceptance of this quotatio	n by signing below:			
Customer: X		/		

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.

Prepared by:
Nate Vaillancourt
ADVANTAGE TRUCK GROUP
220 FRONTAGE RD.
MANCHESTER, NH 03103
Phone:

SPECIFICATION PROPOSAL

Data C	ode	Description	Weight Front	Weight Rear	
Price Level					
PRL-28	8X	WST 47X/49X PRL-28X (EFF:MY25 ORDERS)			
Data Version					
DRL-0	40	SPECPRO21 DATA RELEASE VER 040			
Vehicle Confi	gurati	on			
001-47	70	WESTERN STAR 47X	9,050	6,525	AND THE SHEET SHEET
004-22	25	2025 MODEL YEAR SPECIFIED			
002-00)3	SET FORWARD AXLE - TRUCK	-480	480	
019-00	06	TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560	10	10	
003-00)1	LH PRIMARY STEERING LOCATION			
General Servi	ice				
AA1-00	03	TRUCK/TRAILER CONFIGURATION	151021340115501155011		
AA6-00	01	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)			
99D-0 ⁻	19	CARB CLEAN IDLE LABELS NOT FOR INITIAL REGISTRATION IN STATES REQUIRING CARB EMISSIONS CERTIFICATION (INCLUDES 6X4 INCH LABELS ON LOWER FORWARD OF DRIVER DOOR)			
AF2-99	98	NONE			
A85-01	11	CONSTRUCTION SERVICE			
A84-10	GM	GOVERNMENT BUSINESS SEGMENT			
AA4-0	10	DIRT/SAND/ROCK COMMODITY			
AA5-0	02	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS			
AB1-0	80	MAXIMUM 8% EXPECTED GRADE			
AB5-0	01	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			
995-1	46	WESTERN STAR SEVERE SERVICE WARRANTY			
A66-99	9D	EXPECTED FRONT AXLE(S) LOAD: 20000.0 lbs			

Data Code	Description	Weight Front	Weight Rear	
A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD: 40000.0 lbs			
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 60000.0 lbs			
A70-99D	EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs			
Truck Service				
AA3-018	FRONT PLOW/END DUMP BODY	MANAGEMENT OF THE PROPERTY OF		
AF3-1E7	DONOVAN EQUIPMENT			
Tractor Service				
AA2-005	FLATBED TRAILER			
AH6-001	SINGLE (1) TRAILER			
Engine				
101-3BP	CUM L9 330 HP @ 2200 RPM; 2200 GOV RPM, 1000 LB-FT @ 1200 RPM	-850	-70	
Electronic Paramet	ters			
79A-059	59 MPH ROAD SPEED LIMIT			
79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT			
79G-107	10 MINUTE IDLE SHUTDOWN - CONTINUOUS OVERRIDE WITH CLUTCH AND SERVICE BRAKE			
79K-009	PTO MODE ENGINE RPM LIMIT - 1200 RPM			
79M-002	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED			
79P-004	PTO RPM WITH CRUISE SET SWITCH - 900 RPM			
79Q-004	PTO RPM WITH CRUISE RESUME SWITCH - 900 RPM			
79S-001	PTO MODE CANCEL VEHICLE SPEED - 5 MPH			
79U-001	PTO GOVERNOR RAMP RATE - 25 RPM PER SECOND			
79V-001	FUEL DOSING OF AFTERTREATMENT ENABLED IN PTO MODE-CLEANS HYDROCARBONS AT HIGH TEMPERATURES ONLY			
79W-024	CRUISE CONTROL BUTTON PTO CONTROL			
79X-001	PTO SPEED 1 SETTING - 700 RPM			
79Y-022	PTO SPEED 2 SETTING - 700 RPM			
79Z-019	PTO SPEED 3 SETTING - 700 RPM			
* 80P-998	NO FLEET SPEC FOR PARAMETERIZATION			
80E-001	ENGINE FAN ENABLED WITH RETARDER			
80G-002	PTO MINIMUM RPM - 700			
80L-004	ENABLE DPF REGEN STAY WARM			

Data Code	Description	Weight Front	Weight Rear
80S-001	PTO 1, DASH SWITCH, STATIONARY OPERATION		
80V-001	ENGINE MOUNT PTO, DASH SWTICH ENGAGES PTO MODE, STATIONARY OPERATION		
Engine Equipment			
99C-124	EPA 2010 GHG 2024/CARB 2024 ULTRALOW NOX CONFIGURATION		AND ELECTRICATION OF SERVICE STATE OF ELECTRICATION OF SERVICE STATE OF THE SERVICE STATE OF SERVICE STATE STATE STATE OF SERVICE STATE OF SERVICE STATE
13E-001	STANDARD OIL PAN		
105-015	OIL FILL AND DIPSTICK LOCATED FOR ENHANCED SERVICEABILITY		
014-111	SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER, WITH INSIDE/OUTSIDE AIR AND SNOW DOOR		
124-1E1	DR 12V 200 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	-10	
292-222	(3) DTNA GENUINE, HIGH TEMP AGM STARTING AND CYCLING, MIN 2775CCA, 570RC, THREADED STUD BATTERIES		
290-1AC	PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE OF CAB		
282-013	BATTERY BOX MOUNTED UNDER PASSENGER SEAT		
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
289-006	PLASTIC BATTERY BOX COVER		
293-058	POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	2	
295-029	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
306-015	PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS	2	
107-032	CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
128-032	C-BRAKE BY JACOBS WITH LOW/OFF/HIGH BRAKING DASH SWITCH		
016-1C2	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE		

Data Code	Description	Weight Front	Weight Rear	
28F-015	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH			
239-032	11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT			
237-1CR	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP			
23U-002	13 GALLON DIESEL EXHAUST FLUID TANK	9	3	
23Z-005	UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER			
43X-001	LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP			
242-001	STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD			
273-059	ELECTRONICALLY CONTROLLED VARIABLE SPEED VISCOUS FAN DRIVE			-
276-002	AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED			
122-1H4	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR AND 12 VOLT PREHEATER	10		
110-003	CUMMINS SPIN ON FUEL FILTER			
118-001	FULL FLOW OIL FILTER	•		
266-109	1400 SQUARE INCH VOCATIONAL RADIATOR WITH PROTECTION PACKAGE	20		
103-039	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
261-001	STANDARD CHARGE AIR COOLER PLUMBING			
270-016	RADIATOR DRAIN VALVE			
168-002	LOWER RADIATOR GUARD			
360-013	1350 ADAPTER FLANGE FOR FRONT PTO PROVISION	20		
138-011	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4		
166-005	PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PREHEATER	4		
140-022	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
132-004	ELECTRIC GRID AIR INTAKE WARMER			

	Data Code	Description	Weight Front	Weight Rear	
	155-055	DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	-45		
Trans	mission				
1 020/1100000000000000000000000000000000	342-582	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	-230	-130	
Trans	mission Equi	pment			
AND THE CONTROL OF TH	343-339	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV			
	84B-002	ALLISON VOCATIONAL RATING FOR CONCRETE MIXER APPLICATIONS ONLY AVAILABLE WITH 3000 PRODUCT FAMILIES			
	84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
	84D-020	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 3, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
	84E-000	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
	84F-000	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
	84G-000	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
	84H-000	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		4	
	84N-200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED			
	84P-998	NO TCU-PTO DRIVE INTERFACE			
	85E-009	MAXIMUM ENGINE SPEED FOR PTO ENGAGEMENT 900 RPM			
	85F-034	MAXIMUM ENGINE SPEED FOR PTO OPERATION 2000 RPM			
	353-076	QUICKFIT BODY LIGHTING CONNECTOR AT END OF FRAME, WITH BLUNTCUTS			
	34C-011	ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR			
	362-823	CUSTOMER INSTALLED CHELSEA 280 SERIES PTO			

Data Code	Description	Weight Front	Weight Rear
363-001	PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON		
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
345-078	HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED		
370-006	WATER TO OIL TRANSMISSION COOLER		
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		
Front Axle and Equ	uipment		
400-1AC	CUMMINS-MERITOR MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE	240	
418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS	20	
402-030	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	40	
403-002	NON-ASBESTOS FRONT BRAKE LINING		
419-023	CONMET CAST IRON FRONT BRAKE DRUMS		
427-001	FRONT BRAKE DUST SHIELDS	5	
409-006	FRONT OIL SEALS		
408-016	STEMCO SERIES 340/343/346 TRADITIONAL ALUMINUM FRONT HUB CAPS WITH WINDOW AND RED VENT PLUGS - OIL		
405-003	HALDEX AUTOMATIC FRONT SLACK ADJUSTERS		
536-104	DUAL POWER STEERING GEARS, BENDIX 16- 20K	80	
534-003	4 QUART POWER STEERING RESERVOIR	5	
533-001	OIL/AIR POWER STEERING COOLER	5	
40T-003	SYNTHETIC 40/50W FRONT AXLE LUBE		
Front Suspension			
620-043	9,500# LEFT, 10,500# RIGHT MIXER/PLOW FLAT LEAF FRONT SUSPENSION (20,000#)	250	300000000000000000000000000000000000000
619-002	THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION		
410-001	FRONT SHOCK ABSORBERS		
Rear Axle and Equ	ipment		

	Data Code	Description	Weight Front	Weight Rear	
N	420-024	CUMMINS-MERITOR RS-30-185 30,000# U- SERIES SINGLE REAR AXLE	*	-1,990	
N	450-014	WEBB IRON REAR HUBS		20	
	421-538	5.38 REAR AXLE RATIO			
	424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			
	386-074	MXL 176T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-50	-50	
	388-998	NO INTERAXLE (#3) DRIVELINE			
	452-001	DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20	
	878-018	(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE			
	87B-008	INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH			
N	423-010	MERITOR 16.5X7 P CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, CAST SHOES		95	
	433-002	NON-ASBESTOS REAR BRAKE LINING			
	434-011	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)			
N	451-018	WEBB CAST IRON REAR BRAKE DRUMS		50	
	425-002	REAR BRAKE DUST SHIELDS		5	
	440-006	REAR OIL SEALS			
	426-100	WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		-20	
	428-003	HALDEX AUTOMATIC REAR SLACK ADJUSTERS			
	41T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE			
	42T-001	STANDARD REAR AXLE BREATHER(S)			
Rear	Suspension				
N	622-1DF	30,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD		200	
	621-114	8.5 INCH NOMINAL RIDE HEIGHT (430MM GLOBAL REFERENCE HEIGHT)			
	431-001	STANDARD AXLE SEATS IN AXLE CLAMP GROUP			
	623-005	FORE/AFT CONTROL RODS			
	439-998	NO REAR SHOCK ABSORBERS		-30	
Push	ner / Tag Equip	oment			
	429-998	NO PUSHER/TAG BRAKE DUST SHIELDS			
Brak	e System				
A MARKETON					

	Data Code	Description	Weight Front	Weight Rear	
3	490-1AU	WABCO 4S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH	10 mm		
	871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
	432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
	480-086	BW AD-9SI BRAKE LINE AIR DRYER WITH HEATER			
	479-015	AIR DRYER FRAME MOUNTED			
	460-091	ALUMINUM AIR BRAKE RESERVOIRS, NO TRIPLE OR TORPEDO TANKS	-25	-25	
	477-019	BW DV-2 AUTO DRAIN VALVE WITH HEATER TO WET TANK; DRAIN VALVE CABLES ON ALL OTHER TANKS			
	485-037	CAB BLOW OUT KIT WITH AIR HOSE AND NOZZLE INSIDE LH CAB ENTRY DOOR	2		
Trailer	Connections				
65-Chenenellana	914-025	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND DUST COVERS			
	919-060	(1) ADDITIONAL SWITCH FOR ELEC/AIR SOLENOID W/STATE RETENTION PLUMBED TO BACK OF CAB			
	296-010	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			
	303-025	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME			
Wheelb	ase & Frame				
equestra composito	545-107	4740MM (187 INCH) WHEELBASE, SFA ONLY			
×	546-106	13.0MM X 87.0MM X 311.0MM STEEL FRAME (0.51X3.43X12.24 INCH) 120 KSI	120	410	
	552-029	1575MM (62 INCH) REAR FRAME OVERHANG			
	55W-006	FRAME OVERHANG RANGE: 61 INCH TO 70 INCH	-30	90	
	549-002	24 INCH INTEGRAL FRONT FRAME EXTENSION	120		
	AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 105.12 in			
	AE4-99D	CALC'D FRAME LENGTH - OVERALL: 301.21 in			
	ZF1-99D	FRAME HEIGHT TOP FRONT UNLADEN: 44.55 in			
	ZF2-99D	FRAME HEIGHT TOP FRONT LADEN: 40.7 in			
	ZF3-99D	FRAME HEIGHT TOP REAR UNLADEN: 43.32 in			
	ZF4-99D	FRAME HEIGHT TOP REAR LADEN: 40.3 in			
	553-001	SQUARE END OF FRAME			

	Data Code	Description	Weight Front	Weight Rear	
	559-001	STANDARD WEIGHT ENGINE CROSSMEMBER		E	
	561-001	STANDARD CROSSMEMBER BACK OF TRANSMISSION			
	562-001	STANDARD MIDSHIP #1 CROSSMEMBER(S)	10	10	
	572-078	HEAVY DUTY REAR C-CHANNEL CROSSMEMBER, NON-TOWING		70	
	565-001	STANDARD SUSPENSION CROSSMEMBER		20	
	568-001	STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER			
Chassis	Equipment				
	025-001	UNPOLISHED ALUMINUM WST EQUIPMENT COVERS			
	5CF-001	CLEAR FRAME SPACE REQUESTED			
	556-800	TEMPORARY STEEL BUMPER	-40		
	558-998	NO FRONT TOW HOOKS	-15		
	574-998	NO LICENSE PLATE MOUNTING			
	551-034	CLASS 10.9 THREADED METRIC FASTENERS			
	44Z-002	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE			
Fuel Ta	nks				
	204-151	60 GALLON/227 LITER ALUMINUM FUEL TANK - LH	-5		
	218-006	25 INCH DIAMETER FUEL TANK(S)			
	215-007	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS			
	212-007	FUEL TANK(S) FORWARD			
	664-001	PLAIN STEP FINISH			
	205-002	CHROME FUEL TANK CAP(S)			
	216-020	EQUIFLO INBOARD FUEL SYSTEM			
	202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			
Tires					
In the same of the same of	093-2CC	MICHELIN XZU-S2 315/80R22.5 20 PLY RADIAL FRONT TIRES	100		icegoscopieroscopie de Comitica de Santonia de Antonia de Santonia de Comitica de Comitica de Comitica de Comi
	094-2CM	MICHELIN X WORKS XDY 315/80R22.5 20 PLY RADIAL REAR TIRES		232	
Wheels					
	502-664	ALCOA ULTRA ONE 89U63X 22.5X9.00 10-HUB PILOT 3.12 INSET 10-HD ALUMINUM FRONT WHEELS	-44		999-999-99-1995-1996-2007-1

	Data Code	Description	Weight Front	Weight Rear
	505-356	ALCOA ULTRA ONE 89U64X 22.5X9.00 10-HUB PILOT 5.99 INSET ALUMINUM REAR WHEELS		-56
	496-011	FRONT WHEEL MOUNTING NUTS		
	497-011	REAR WHEEL MOUNTING NUTS		
	498-011	NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		
Cab E	xterior	The second of th		
14MES MARKET	829-053	111.6 INCH BBC CONVENTIONAL ALUMINUM CAB		
	82A-028	STAINLESS STEEL CAB ACCENT MOLDING		
	667-001	FRONT FENDERS		
	754-017	BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	10	
	678-066	INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES		
	65X-010	BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS		
	640-016	X-SERIES STEEL REINFORCED ALUMINUM CAB		
	644-049	X-SERIES VOCATIONAL HOOD WITH ACCESS HATCH	10	
	67U-001	HOOD OPENING ASSIST WITH LOCKING STRUT		
	652-016	WESTERN STAR NAMEPLATES		
	727-012	DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS		
	726-002	DUAL ELECTRIC HORNS		
	575-001	REAR LICENSE PLATE MOUNT END OF FRAME		
	327-012	SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS	2	
	312-095	DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM		
	302-073	VISOR MOUNTED LED MARKER LIGHTS		
	314-824	WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH DUAL CONNECTIONS AT BUMPER		
	311-001	DAYTIME RUNNING LIGHTS		
	294-1AY	INTEGRAL LED STOP/TAIL/BACKUP LIGHTS		
	300-043	LED SIDE TURN SIGNAL		
	318-1D7	(2) FLUSH LED UTILITY LIGHTS MOUNTED BACK OF CAB/SLEEPER	6	
	31K-800	SWITCH & WIRING TO LH/RH OF DASH FOR C/F MIRROR MOUNTED UTILITY LIGHTS		

	Data Code	Description	Weight Front	Weight Rear
	744-105	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BRIGHT C-BAR	20	
	796-001	102 INCH EQUIPMENT WIDTH		
	743-209	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS		
	74A-001	RH DOWN VIEW MIRROR		
	729-001	STANDARD SIDE/REAR REFLECTORS		
	677-098	UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER		
	764-020	STAINLESS STEEL EXTERIOR SUN VISOR WITH INTEGRAL MARKER LIGHTS	16	
	768-064	SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH		
	663-019	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD		
	659-006	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR		
Cab In	terior			
For Dell's Residential	055-015	X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE	STELL SCRIPT (SOCIAL SETTING SCRIPTION OF STREET SOCIAL CONTINUES OF C	
	707-1CW	QUARRY GRAY VINYL BASE LEVEL INTERIOR		
	70K-016	CARBON WITH BASE BLACK ACCENT		
	772-035	BLACK MATS WITH ADDED FLOOR HEAT AND NOISE INSULATION		
	785-014	(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY		
	691-001	FORWARD ROOF MOUNTED CONSOLE		
	693-019	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
	741-015	(2) COAT HOOKS ON BACKWALL OF CAB		
	738-021	DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
	720-035	2-1/2 LB. FIRE EXTINGUISHER MOUNTED INBOARD OF DRIVER SEAT	5	
	170-045	STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY		
	698-001	RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
	739-033	STANDARD INSULATION		
	324-1B3	STANDARD LED CAB LIGHTING		
		NO SECURITY DEVICE		

	Data Code	Description	Weight Front	Weight Rear
	657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
	78G-003	KEY QUANTITY OF 3		
	655-028	LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION		
	64C-003	BLACK DOOR HANDLES		
	722-028	TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10	
	756-1J6	PREMIUM 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 2 AIR LUMBAR, INTEGRATED CUSHION EXTENSION, TILT AND ADJUSTABLE SHOCK	20	
	760-294	BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT		
	757-001	BLACK SUSPENSION COVER FOR AIR DRIVER SEAT	2	
	759-007	DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS		
	758-135	BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO		
	761-138	BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH NO LOGO		
	763-1AB	3 POINT HIGH VISIBILITY ORANGE ADJUSTABE D-RING RETRACTOR DRIVER AND FIXED D-RNG RETRACTOR PASSENGER SEAT BELTS		
	532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
	540-044	4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		
	765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS		
Instrum	nents & Contr	ols		
Bridge of the Land Control of the Land	185-004	STANDARD FOOT PEDAL SYSTEM		
	106-002	ELECTRONIC ACCELERATOR CONTROL		
	870-001	BLACK GAUGE BEZELS		
	734-018	STANDARD CENTER INSTRUMENT PANEL		
	838-001	(1) PNEUMATIC SINGLE BRAKE APPLICATION AIR GAUGE		
	840-001	DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
	198-003	DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS	2	
	721-001	97 DB BACKUP ALARM		3

Data Code	Description	Weight Front	Weight Rear	
149-015	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES			***************************************
156-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			
811-044	PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY			
81B-003	DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY			
160-045	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH			
844-001	2 INCH ELECTRIC FUEL GAUGE			
148-072	ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS			
856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE	•		
854-998	NO ENGINE OIL TEMPERATURE GAUGE			
852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE			
864-001	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			
867-004	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER			
830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
372-123	PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE			
736-998	NO OBSTACLE DETECTION SYSTEM	•		
73K-998	NO SIDE OBJECT DETECTION SYSTEM			
72K-998	NO REVERSE PROXIMITY SENSOR			
72J-99 8	NO DR ASSIST SYSTEM	•		
49B-998	NO VEHICLE STABILITY ADVISOR OR CONTROL			
73B-998	NO LANE DEPARTURE WARNING SYSTEM			
35M-010	1 QUICKFIT PROGRAMABLE MODULE (QPM/XMC)	10		
6TS-008	(2) TMC RP1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND PASSENGER SIDE REMOVABLE DASH PANEL (1) CENTER OF OVERHEAD CONSOLE			
1U1-002	TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE			
746-136	AM/FM/WB WORLD TUNER RADIO WITH AUXILIARY INPUT, J1939			

Data Code	Description	Weight Front	Weight Rear	
747-001	DASH MOUNTED RADIO			
750-041	STANDARD SPEAKER SYSTEM			
753-998	NO AM/FM RADIO ANTENNA			
748-044	UNIDEN PC78LTX FACTORY INSTALLED CB RADIO WITH SWR METER	5		
749-001	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION			
751-001	SINGLE REMOTE SPEAKER WITH LEAD FOR 2- WAY RADIO			
752-004	SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD			
75W-001	HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS			
810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			
812-032	ELECTRONIC 2500 RPM TACHOMETER			
813-1C8	DETROIT CONNECT PLATFORM HARDWARE			
8D1-315	5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES			
162-002	IGNITION SWITCH CONTROLLED ENGINE STOP			
329-133	FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO BETWEEN SEATS, BLUNTCUT			
4C1-025	HARDWIRE SWITCH #1, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
4C2-026	HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER			
4C3-017	HARDWIRE SWITCH #3,0N/OFF LATCHING, 10 AMPS BATTERY POWER			
4C4-016	HARDWIRE SWITCH #4, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
81Y-005	PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY			
482-001	BW TRACTOR PROTECTION VALVE			
883-001	TRAILER HAND CONTROL BRAKE VALVE	2		
842-006	DIGITAL TURBO AIR PRESSURE IN DRIVER DISPLAY			
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			
304-030	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS			

Prepared by:
Nate Vaillancourt
ADVANTAGE TRUCK GROUP
220 FRONTAGE RD.
MANCHESTER, NH 03103
Phone:

	Data Code	Description	Weight Front	Weight Rear	
	882-004	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR			
	299-020	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT			
	4E1-013	PROGRAMMABLE SWITCHES/INDICATORS LOCATED IN AUXILIARY PANEL			
	48H-004	QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS			
•	4CG-005	5 EXTRA PROGRAMMABLE SWITCHES/INDICATORS			
	;	\$A1A0071ZZ,A1B0230ZZ,A1C0192ZZ,A1D0000ZZ ,A1E000	0ZZ		
	48C-004	QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS			
	87G-005	OPTIONAL AIR SWITCH 1 WITH NO INTLK			
Design					
	065-000	PAINT: ONE SOLID COLOR			
Color					
	980-7ED	CAB COLOR A: L0180EY MAROON ELITE EY			
	986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT			
Certific	ation / Com	pliance			
	996-001	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS			
Second	lary Factory	Options			
	998-032	CORPORATE PDI CENTER OPTION INSTALLATION/MODIFICATION ONLY			
Clear F	rame Space	Details			
	5LA-001	CFS,LH,OB,#1,START 1" BOC			
	5LB-072	CFS,LH,OB,#1, 72" LONG			
	5MA-001	CFS,RH,OB,#1,START 1" BOC			
	5MB-073	CFS,RH,OB,#1, 73" LONG			
Sales F	rograms				
	PMY-3X3	STARQUOTE 47X/49X SALES PROGRAM			
					STATE OF THE PARTY

TOTAL VEHICLE SUMMARY

Weight Summary

Prepared by:
Nate Vaillancourt
ADVANTAGE TRUCK GROUP
220 FRONTAGE RD.
MANCHESTER, NH 03103
Phone:

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	8426 lbs	5872 lbs	14298 lbs
Total Weight ⁺	8426 lbs	5872 lbs	14298 lbs

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

^(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.