


		ISTING LEGEND:	PR	OPOSED LEGEND:
	• ب ب ب	IRON BOUND/REBAR ~FND~ CONCRETE/GRANITE BOUND ~FND~ UTILITY POLE GUY WIRE SIGNAGE	•	3/4" REBAR W/ ID CAP ~TBS~ 1/2" REBAR W/EASEMENT CAP ~TBS~ GRANITE BOUND ~TBS~
	<u>↓</u> ♦	TEST PIT	(E101) E6	DETAIL SHEET / DETAIL
	 ↔ ₩ 	TEMPORARY BENCHMARK (T.B.M.) WELL	F176 F175	CONTOUR MINOR, PROPOSED Contour Major, proposed
		BUILDING SETBACK LINE POORLY DRAINED JURISDICTIONAL WETLAND LINE VERY POORLY DRAINED JURISDICTIONAL WETLAND LINE 50' POORLY DRAINED WETLAND BUFFER NRCS SOIL DELINEATION LINE SITE SPECIFIC SOIL LINE		ROAD CENTERLINE SHOULDER DRAIN CULVERT W/ FLARED END SECTIO UNDERDRAIN GUARD RAIL PROPOSED EASEMENT LINE
	HU OHU OHU OHU OHU OHU OHU OHU OHU OHU O	LIMIT OF SOIL SURVEY OVERHEAD UTILITIES LINE UNDERGROUND UTILITIES LINE EXISTING DRAIN CULVERT CONTOUR MINOR, EXISTING CONTOUR MAJOR, EXISTING CONSERVATION EASEMENT LINE	2002 2002 2002	RIP RAP STORMWATER BEST MANAGEMENT PRAC BERM
		TREELINE NHDES PROTECTIVE WELL RADIUS RED PINE PLANTATION MATCH LINE MATCH POINT		DRAIN MANHOLE W/STRUCTURE CATCH BASIN W/ STRUCTURE
	Qu	FIRE DEPARTMENT CONNECTION LIGHT, POLE MOUNTED	₩ ₩ — — UGE— — UGE— — UGE—	STORMWATER BMP OUTLET STRUCTURE J.BOX UNDERGROUND UTILITY
	CsB S.C.R.D. TYP	SOIL SERIES NRCS SOIL LABEL STRAFFORD COUNTY REGISTRY OF DEEDS TYPICAL	-Ŏ¤ Ŏ	EXISTING LIGHT TYPE "A" MOUNTED ON PROPOSED LIGHT TYPE "B" MOUNTED ON
	FND	FOUND POORLY DRAINED JURISDICTIONAL WETLAND HATCH		PROPOSED EFFLUENT FORCEMAIN PROPOSED GRAVITY SEWER SERVICE
			E175.31	EFFLUENT DISPOSAL AREA EXISTING SPOT GRADE PROPOSED SPOT GRADE
	VIATION LEGEND:		- SS SS SS - P/C P/C	FLOW ARROW SAW CUT & MILL SILT FENCE / EROSION MIX BERM FILTREXX 8" – 12" SILT SOXX AS SPECI PERIMETER CONTROL (SEE E-101)
<i>ABBRE</i> E.O.P.	EDGE OF PAVEMENT		- c c c	CONSTRUCTION FENCE
B.C.C.	BITUMINOUS CONCRETE CU	RB		PERMANENT WETLAND BUFFER IMPACT
S.G.C.	SLOPED GRANITE CURB			TEMPORARY WETLAND BUFFER IMPACT
C.C.C.	CAST-IN-PLACE CONCRETE	E CURB		SNUW STURAGE
BITUM.	BITUMINOUS			
E.S.H.W.T	ESTIMATE SEASONAL HIGH WATER TABLE		LEGEND:	
TYP	TYPICAL		TREES:	
U.G.E	UNDER GROUND ELECTRIC		کریے کے AR – Acer rubrum /	Red Maple 3" caliper (15 TOTAL)
O.H.U.	OVERHEAD ELECTRIC / UTI			
CLDI DI	CONCRETE LINED DUCTILE	IKUN	Cornus Controversa /	' Pagoda Dogwood 2" caliper (3)
F.P.	FIRE PROTECTION			• • • • •
FDC	FIRE DEPARTMENT CONNEC	CTION	Picea Glauca / White	Spruce 6' height (8)
U.D.	UNDER DRAIN		EVICTINO MADIE TOPE	
C.O.	CLEAN OUT		EXISTING MAPLE TREE	
TYP.	INVERT			
ELEV.				
HDPE RCP	HIGH DENSITY POLYETHYLE REINFORCED CONCRETE PIF			
RECB	ROLLED EROSION CONTROL			
F.G.	FINISHED GRADE			
E <i>.</i> G.	EXISTING GRADE			
E.T.W.	EDGE OF TRAVELED WAY			
T.B.R.	TO BE REMOVED			
PL	PROPERTY LINE			
EL	EASEMENT LINE			
CL	CENTER LINE CUBIC FEET			
P.C.	POINT OF CURVATURE			
P.T.	POINT OF TANGENCY			
P.V.C.	POINT OF VERTICAL CURVE			
P.V.I.	POINT OF VERTICAL INTERS	SECTION		
P.V.T.	POINT OF VERTICAL TANGE	INCY		
EX.	EXISTING			
PROP. STA.	PROPOSED			
STA. BMP	BEST MANAGEMENT PRACT	ICE		
	FEET / FEET			
'/.				
	TEST PIT			
'/, TP FND	TEST PIT FOUND			

{ } DBL () ~ {SIZE} DOUBLE BROKEN LINE (COLOR W=WHITE, Y=YELLOW)



SI	TE PLAN NOTES:	STANDARD CONSTRUCTION NOTES:
1.)	I HEREBY CERTIFY THAT, TO THE BEST OF MY KNOWLEDGE & BELIEF, THIS PARCEL DOES NOT FALL WITHIN THE FLOOD PLAIN. FLOOD HAZARD REF.: FEMA, COMMUNITY# - 330178, MAP# - 33017C0305E, DATED: SEPTEMBER 30, 2015.	1.) SEE EROSION & SEDIMENT CONTROL PLANS FOR DETAIL CONTROL (MULCH BERM / FENCE / SILT SOXX).
2.)	PROPERTY LINE INFORMATION HAS BEEN OBTAINED FROM A SURVEY PERFORMED BY BERRY SURVEYING & ENGINEERING IN SPRING OF 2023 WITH AN ERROR OF CLOSURE GREATER THAN 1 IN 10,000 UNDER NO SNOW CONDITIONS.	 2.) TWO ON SITE BENCHMARKS ARE PROVIDED. BS&E IS T ADDITIONAL BENCHMARKS PRIOR TO CONSTRUCTION. 3.) EXISTING ARE PROVIDED AT 2' INTERVALS AND PROPOS
3.)	AS-BUILT PLANS OF THE SITE SHALL BE SUBMITTED ON A REPRODUCIBLE MYLAR MEDIUM AND IN A DIGITAL DXF FORMAT ON DISK TO THE TOWN OF BARRINGTON PLANNING OFFICE UPON COMPLETION OF PROJECT. AS-BUILT PLANS SHALL BE PREPARED AND CERTIFIED CORRECT BY A L.L.S. OR P.E.	ARE PROVIDED AT 1' INTERVALS WITH DRAINAGE FEATU PRECISE INTERVALS. 4.) SEE UTILITY PLANS FOR DETAILS ON THE PROPOSED EF
4.)	TOPOGRAPHIC SURVEY PERFORMED BY BERRY SURVEYING & ENGINEERING IN SPRING OF 2023 UNDER NO SNOW CONDITIONS AND IS SHOWN AT 2 FOOT INTERVALS	AND UNDERGROUND ELECTRIC LINES SHOWN.
5.)	DATUM: PROJECT DATUM IS BASED ON GPS COORDINATES ESTABLISHED WITH A CARLSON BRX7 SURVEY GRADE GPS RECEIVERS IN SPRING OF 2023 AND REPRESENTED IN NEW HAMPSHIRE STATE PLANE COORDINATES NAD 1983 AND VERTICALLY BY NAVD 1988.	BY BERRY SURVEYING & ENGINEERING AND IS ENCLOSE PACKAGE.
6.)	UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVE AND BELOW GROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR. ANY UTILITY CONFLICTS SHOULD BE REPORTED IMMEDIATELY TO THE DESIGN ENGINEER.	 6.) CONTRACTOR SHALL TAKE SPECIAL CARE IN NOT DISTUMONUMENTS BOUNDS, AND OR BENCHMARKS WITHOUT F PROVISIONS FOR RELOCATION. 7.) THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES A
8.)	ALL ON-SITE UTILITIES SHALL BE INSTALLED UNDERGROUND WITH THE EXCEPTION OF POSSIBLY ONE DROP POLES REQUIRED BY EVERSOURCE. THE SUBJECT PARCELS ARE SERVED BY ON SITE WATER AND EFFLUENT DISPOSAL.	APPROXIMATE WAY ONLY AND HAVE NOT BEEN INDEPEN BY THE OWNER OR ITS REPRESENTATIVE. THE CONTRA DETERMINE THE EXACT LOCATION OF ALL EXISTING UTIL COMMENCING WORK AND AGREES TO BE FULLY RESPON AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY T FAILURE TO LOCATE EXACTLY AND TO PRESERVE ANY
9.)	ALL MATERIALS AND METHODS OF CONSTRUCTION SHALL CONFORM TO TOWN REGULATIONS AND THE LATEST EDITION OF THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION'S STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.	UNDERGROUND UTILITIES CALL "DIG-SAFE" 1-888-DIGS AT LEAST 72 HOURS BEFORE COMMENCING CONSTRUCT
10.)	ALL EROSION CONTROL NOTES SHALL INCLUDE PROVISIONS FOR CONSTRUCTION SEQUENCING, TEMPORARY EROSION CONTROL MEASURES, AND PERMANENT STANDARDS SUCH AS LOAM SPREAD RATE FOR DISTURBED AREAS, RATES OF LIME, TYPE AND RATES FOR FERTILIZER, AND SEED AND MULCH MIXTURE WITH RATES OF APPLICATION.	8.) WHERE AN EXISTING UNDERGROUND UTILITY IS FOUND T WITH THE PROPOSED WORK, THE LOCATION, ELEVATION UTILITY SHALL BE ACCURATELY DETERMINED WITHOUT D CONTRACTOR, AND THE INFORMATION FURNISHED TO TH RESOLUTION OF THE CONFLICT.
11.)	THE LIMITS OF CONSTRUCTION DISTURBANCE SHALL BE STAKED, FLAGGED AND CLEARLY IDENTIFIED PRIOR TO THE COMMENCEMENT OF SITE WORK.	9.) THE CONTRACTOR SHALL MAKE ALL ARRANGEMENTS FO ALTERATION AND ADJUSTMENT OF GAS (IF APPLICABLE) TELEPHONE AND ANY OTHER PRIVATE UTILITIES BY THE
12.)	A LETTER OF CREDIT FOR THE COST OF RE-VEGETATING ALL DISTURBED AREAS ON THE SITE SHALL BE SUBMITTED PRIOR TO ANY EARTH DISTURBING ACTIVITY OCCURS. COORDINATE WITH TOWN OF BARRINGTON, LAND USE OFFICE.	COMPANIES. 10.) AREAS OUTSIDE THE LIMITS OF PROPOSED WORK DIST
13.)	A PRE-CONSTRUCTION CONFERENCE WITH THE DEVELOPER, THE DESIGN ENGINEER, THE EARTHWORK CONTRACTOR, AND THE TOWN ENGINEER SHALL OCCUR PRIOR TO ANY EARTH DISTURBING ACTIVITY.	CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY TO THEIR ORIGINAL CONDITION AT THE CONTRACTOR'S DISTURBANCE OUTSIDE AREAS SHOWN TO BE APPROVI ENGINEER.
14.)	BUILDING ADDRESSES SHALL BE ASSIGNED BY THE BUILDING INSPECTOR AT THE TIME OF ISSUANCE OF A BUILDING PERMIT. (NOT APPLICABLE)	11.) THE TERM "PROPOSED" (PROP.) MEANS WORK TO BE USING NEW MATERIALS, OR, WHERE APPLICABLE, RE-L
15.)	THE FOLLOWING FEDERAL, STATE AND LOCAL PERMITS HAVE BEEN ISSUED FOR THE SUBJECT PROPERTY: NHDES ALTERATION OF TERRAIN PERMIT (PENDING) US EPA NOI & SWPPP (PENDING) NATURAL HERITAGE BUREAU NHB24-0311 NH DIVISION OF HISTORICAL RESOURCES (PENDING)	MATERIALS IDENTIFIED AS "REMOVE & RESET" (R & R 12.) ALL SYMBOLS, WORDS, TRANSVERSE MARKINGS (STOP CROSSWALK LINES, AND RAILROAD SYMBOLS), LANE LI
16.)	NH DIVISION OF THISTONICAL RESOURCES(FENDING)NHDOT DRIVEWAY PERMIT06-027-413 (TO BE MODIFIED)NOTE THAT THE PROJECT IS SUBJECT TO THE EPA NPDES PHASE II. THE NOTICE OF INTENT (NOI) MUST BE	OTHER MARKINGS NOTED WITH {T} SHALL BE THERMOF 13.) ALL ELEVATIONS TO BE VERIFIED BY THE CONTRACTOF CONSTRUCTION. THE DESIGN ENGINEER IS TO BE NOTIF
	FILED ALONG WITH A STORMWATER POLLUTION PREVENTION PLAN (SWPPP). WEEKLY INSPECTIONS WILL BE CONDUCTED BY THE DESIGN ENGINEER OR AFTER A STORM EVENT OF GREAT THAN 0.25". THIS SITE PLAN PROPOSES 162,000 Sq. Ft., (3.72 Ac.) OF DISTURBANCE.	OF ANY DISCREPANCY. TEMPORARY BENCHMARKS (T.B PROVIDED BY THE DESIGN ENGINEER. 14.) UPON FINAL COMPLETION AND 85% STABILIZATION THE
	CALL DIG SAFE PRIOR TO BEGINNING WORK (1-888-344-7233) ALL CONSTRUCTION SHALL CONFORM TO THE STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION	SYSTEM IS TO BE CLEANED OF ALL DEBRIS TO INCLUE OF THE BASINS.
10.)	STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION. CONSTRUCTION SHALL ALSO CONFORM TO THE TOWN OF BARRINGTON POLICIES AND PRACTICES, AND TOWN OF BARRINGTON SITE PLAN REVIEW REGULATIONS.	15.) ALL CATCH BASINS ARE TO HAVE BOOTS INSTALLED (AND OUTLETS. CATCH BASINS ARE TO HAVE NHDOT T AND DRAIN MANHOLES ARE TO HAVE LIFTMATE MANH(
19.)	WRITTEN DIMENSION ON THIS PLAN TAKE PRECEDENCE OVER SCALED DIMENSIONS. THE CONTRACTOR SHALL USE CAUTION WHEN SCALING REPRODUCED PLANS. IN THE EVENT OF A CONFLICT BETWEEN THIS PLAN SET AND ANY OTHER DRAWINGS AND/OR SPECIFICATIONS, THE ENGINEER SHALL BE NOTIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. CONTRACTOR IS TO CONFIRM ALL ELEVATIONS. CONFLICTS WILL BE REPORTED TO THE	16.) ALL DRAINAGE PIPE IS TO BE HDPE N-12. INDIVIDUAL SPECIFIED, RECYCLED PIPE IS APPROVED FOR PROJEC HDPE PIPE "GREEN PIPE" IS ACCEPTABLE FOR THIS P
20.)	DESIGN ENGINEER PRIOR TO CONSTRUCTION. THERE IS CLEAR SIGHT DISTANCE IN BOTH THE NORTH AND SOUTH DIRECTIONS AT THE DRIVEWAY ENTRANCE OF TURBOCAM ONTO ROUTE 125/CALEF HIGHWAY.	17.) ALL BASINS AND DRAINS ARE PROPOSED WITH NO SU BASINS WITHIN ANY GRASS LINED AREAS OUTSIDE THE HAVE "BEE HIVE" GRATES TO NOT ALLOW FOR ENTRAI ANIMALS IN THE STRUCTURE. OUTLET CONTROL STRU
21.)	EXTERIOR LIGHTING SHALL BE CUT-OFF TYPE FIXTURES AND SHALL PROVIDE LIGHTING DIRECTED ON-SITE ONLY.	HAVE SUMPS. IF REQUIRED TO BE INSTALLED DURING PRE-CASTING PROCESS, THEY ARE TO BE FILLED WITH BASINS ARE TO HAVE NH STANDARD FRAMES AND GR
	CONTRACTOR SHALL COORDINATE ALL ELECTRICAL INSTALLATIONS WITH EVERSOURCE AT (603) 436-7708. ALL ELECTRIC CONDUIT INSTALLATION SHALL BE INSPECTED BY EVERSOURCE PRIOR TO BACKFILL. A 48-HOUR MINIMUM NOTICE IS REQUIRED.	NORTH AMERICA. PLEASE NOTE SOME GRATES ARE SF THE LOCATION AND USE AND ARE CALLED OUT ON TH PLANS. GRATES ARE TO BE INSTALLED BINDER FLUSI PAVE. UPON PROJECT COMPLETION FRAMES AND GRA CUT AND RIM RAISED TO FINAL PAVEMENT SURFACE.
	CONTRACTOR SHALL COORDINATE ALL CABLEINSTALLATIONS WITH BREEZELINE AT (888) 536-9600, AS	ENSURE STORMWATER ENTERS THE SYSTEM AS DESIGN INTERIM CONSTRUCTION PERIOD.
,	APPLICABLE. IF THE EARTHWORK IS PERFORMED DURING FREEZING WEATHER. EXPOSED SUBGRADES ARE SUSCEPTIBLE TO	18.) SEE GRADING PLANS AND STORMWATER BMP PLANS.
25.)	FROST. NO FILL OR UTILITIES SHALL BE PLACED ON FROZEN GROUND. THIS WILL LIKELY REQUIRE REMOVAL OF A FROZEN SOIL CRUST AT THE COMMENCEMENT OF EACH DAY'S OPERATION. THE FINAL SUBGRADE ELEVATION WOULD ALSO REQUIRE AN APPROPRIATE DEGREE OF INSULATION AGAINST FREEZING.	
26.)	PLACEMENT OF BORROW MATERIALS SHALL BE PERFORMED IN A MANNER THAT PREVENTS LONG TERM DIFFERENTIAL SETTLEMENT. EXCESSIVELY WET MATERIALS SHALL BE STOCKPILED AND ALLOWED TO DRAIN BEFORE PLACEMENT. FROZEN MATERIAL SHALL NOT BE USED FOR CONSTRUCTION. VOIDS BETWEEN STONES AND CLUMPS OF MATERIAL SHALL BE FILLED WITH FINE MATERIALS.	
27.)	LIST ANY VARIANCES OR SPECIAL EXCEPTIONS GRANTED BY THE ZONING BOARD OF ADJUSTMENT FOR THIS PROJECT: NONE	
28.)	REQUIRED EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO ANY DISTURBANCE OF THE SITES SURFACE AREA AND SHALL BE MAINTAINED THROUGH THE COMPLETION OF ALL CONSTRUCTION ACTIVITIES. IF DURING CONSTRUCTION IT BECOMES APPARENT THAT ADDITIONAL EROSION CONTROL MEASURES ARE REQUIRED TO STOP ANY EROSION ON THE CONSTRUCTION SITE DUE TO ACTUAL SITE CONDITIONS, THE OWNER SHALL BE REQUIRED TO INSTALL THE NECESSARY EROSION PROTECTION AT NO EXPENSE TO THE TOWN.	WAIVER REQUESTS: SITE REVIEW REGULATION ARTICLE 4.12.2 TABLE #8: UTILIZE MEDIU LOW ACTIVITY USE & AVERAGE LEVELS ABOVE PRESCRIBED
29.)	SNOW STORAGE AREAS ARE AS SHOWN ON THIS SITE PLAN, WHICH PROVIDES FOR APPROXIMATELY 31,337 SQUARE FEET OF STORAGE. THIS REPRESENTS GREATER THAN A 6:1 RATIO. AREAS ARE SHOWN AS CROSS HATCHED ON THE DETAIL SITE PLAN.	SITE REVIEW REGULATION ARTICLE 4.7.7(2): MINIMUM DRAINAGE PIL
30.)	THE APPLICANT IS ABLE TO MAKE LIKE CHANGES TO PRODUCTS SO LONG AS THE DESIGN ENGINEER APPROVES THAT THEY MEET THE DESIGN INTENT. THE DESIGN ENGINEER IS TO NOTE THE PROPOSED PRODUCT CHANGE AND SEND REQUEST FOR REVIEW TO THE TOWN ENGINEER FOR APPROVAL.	
31.)	THE SITE WORK HOURS SHALL BE LIMITED TO MONDAY-FRIDAY 7AM-6PM, SATURDAY 9AM-4PM WITH NO SUNDAY HOURS. HOURS OF CONSTRUCTION SHALL BE DOCUMENTED ON A SITE CONSTRUCTION SIGN ALONG WITH THE CONTACT INFORMATION FOR THE GENERAL CONTRACTOR.	
32.)	IF, DURING CONSTRUCTION, IT BECOMES APPARENT THAT DEFICIENCIES EXIST IN THE APPROVED DESIGN DRAWINGS, THE OWNERS SHALL BE REQUIRED TO CORRECT THE DEFICIENCIES TO MEET THE REQUIREMENTS OF THE REGULATIONS AT NO EXPENSE TO THE TOWN.	
33.)	IF, DURING CONSTRUCTION, IT BECOMES APPARENT THAT ADDITIONAL EROSION CONTROL MEASURES ARE REQUIRED TO STOP ANY EROSION ON THE CONSTRUCTION SITE DUE TO ACTUAL SITE CONDITIONS, THE OWNER SHALL BE REQUIRED TO INSTALL THE NECESSARY EROSION PROTECTION AT NO EXPENSE TO THE TOWN.	
34.)	ALL MATERIALS AND METHODS OF CONSTRUCTION SHALL CONFORM TO TOWN REGULATIONS AND THE LATEST EDITION OF THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION'S STANDARD SPECIFICATIONS FOR ROAD	
35.)	AND BRIDGE CONSTRUCTION. THE FOLLOWING CONDITIONAL USE PERMIT IS REQUESTED FOR THE PROJECT: NONE	FOR TOWN APPROVAL PURPOSES :

STANDARD CONSTRUCTION NOTES:

- SEDIMENT CONTROL PLANS FOR DETAILS ON PERIMETER CH BERM / FENCE / SILT SOXX).
- ENCHMARKS ARE PROVIDED. BS&E IS TO PROVIDE INCHMARKS PRIOR TO CONSTRUCTION.
- PROVIDED AT 2' INTERVALS AND PROPOSED CONTOURS AT 1' INTERVALS WITH DRAINAGE FEATURES AT MORE /ALS.
- ANS FOR DETAILS ON THE PROPOSED EFFLUENT, WATER, UND ELECTRIC LINES SHOWN.
- TIONS INFORMATION IS BASED ON A SURVEY PERFORMED VEYING & ENGINEERING AND IS ENCLOSED IN THIS
- HALL TAKE SPECIAL CARE IN NOT DISTURBING EXISTING UNDS, AND OR BENCHMARKS WITHOUT FIRST MAKING RELOCATION.
- OF EXISTING UNDERGROUND UTILITIES ARE SHOWN IN AN AY ONLY AND HAVE NOT BEEN INDEPENDENTLY VERIFIED OR ITS REPRESENTATIVE. THE CONTRACTOR SHALL EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE ORK AND AGREES TO BE FULLY RESPONSIBLE FOR ANY GES WHICH MIGHT BE OCCASIONED BY THE CONTRACTOR'S CATE EXACTLY AND TO PRESERVE ANY AND ALL UTILITIES CALL "DIG-SAFE" 1-888-DIGSAFE (344-7233) OURS BEFORE COMMENCING CONSTRUCTION.
- TING UNDERGROUND UTILITY IS FOUND TO CONFLICT OSED WORK, THE LOCATION, ELEVATION AND SIZE OF THE BE ACCURATELY DETERMINED WITHOUT DELAY BY THE ND THE INFORMATION FURNISHED TO THE ENGINEER FOR THE CONFLICT.
- OR SHALL MAKE ALL ARRANGEMENTS FOR THE D ADJUSTMENT OF GAS (IF APPLICABLE), ELECTRIC. ANY OTHER PRIVATE UTILITIES BY THE UTILITY
- E THE LIMITS OF PROPOSED WORK DISTURBED BY THE OPERATIONS SHALL BE RESTORED BY THE CONTRACTOR INAL CONDITION AT THE CONTRACTOR'S EXPENSE. OUTSIDE AREAS SHOWN TO BE APPROVED BY DESIGN
- OPOSED" (PROP.) MEANS WORK TO BE CONSTRUCTED ATERIALS, ÒR, WHERE APPLICABLE, RE-USING EXISTING ENTIFIED AS "REMOVE & RESET" (R & R)
- WORDS, TRANSVERSE MARKINGS (STOP BARS, INES. AND RAILROAD SYMBOLS). LANE LINES. AND ALL NGS NOTED WITH {T} SHALL BE THERMOPLASTIC.
- NS TO BE VERIFIED BY THE CONTRACTOR PRIOR TO THE DESIGN ENGINEER IS TO BE NOTIFIED IMMEDIATELY EPANCY. TEMPORARY BENCHMARKS (T.B.M.) ARE TO BE THE DESIGN ENGINEER.
- OMPLETION AND 85% STABILIZATION THE DRAINAGE BE CLEANED OF ALL DEBRIS TO INCLUDE THE PUMPING
- ASINS ARE TO HAVE BOOTS INSTALLED ON ALL INLETS CATCH BASINS ARE TO HAVE NHDOT TYPE "B" GRATES ANHOLES ARE TO HAVE LIFTMATE MANHOLE COVERS.
- PIPE IS TO BE HDPE N-12. INDIVIDUAL PIPE SIZES ARE CYCLED PIPE IS APPROVED FOR PROJECT SITE, RECYCLED REEN PIPE" IS ACCEPTABLE FOR THIS PROJECT SITE.
- ND DRAINS ARE PROPOSED WITH NO SUMPS OR HOODS. ANY GRASS LINED AREAS OUTSIDE THE ROADWAY WILL E" GRATES TO NOT ALLOW FOR ENTRAPMENT OF STRUCTURE. OUTLET CONTROL STRUCTURES WILL NOT F REQUIRED TO BE INSTALLED DURING THE PROCESS, THEY ARE TO BE FILLED WITH STONE ON SITE. O HAVE NH STANDARD FRAMES AND GRATES MADE IN A. PLEASE NOTE SOME GRATES ARE SPECIALIZED FOR AND USE AND ARE CALLED OUT ON THE GRADING S ARE TO BE INSTALLED BINDER FLUSH PRIOR TO BASE PROJECT COMPLETION FRAMES AND GRATES ARE TO BE RAISED TO FINAL PAVEMENT SURFACE. THIS IS TO WATER ENTERS THE SYSTEM AS DESIGN DURING THE FRUCTION PERIOD.

ARTICLE 4.12.2 TABLE #8: UTILIZE MEDIUM ACTIVITY LIGHTING LEVELS FOR A & AVERAGE LEVELS ABOVE PRESCRIBED: PENDING ARTICLE 4.7.7(2): MINIMUM DRAINAGE PIPE DESIGN VELOCITY: PENDING ARTICLE 4.7.7(3): MINIMUM PIPE DEPTH OF 3': PENDING

> THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO.

\overline{UT}	ILITY NOTES:	
1.)	UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVE AND BELOW GROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR. ANY UTILITY CONFLICTS SHOULD BE REPORTED IMMEDIATELY TO THE DESIGN ENGINEER.	SIGN ID N
2.)	PROTECTION OF SUBGRADE: THE CONTRACTOR SHALL BE REQUIRED TO MAINTAIN STABLE, DE-WATERED SUBGRADES, TRENCHES, AND OTHER AREAS DURING CONSTRUCTION. SUBGRADE DISTURBANCE MAY BE INFLUENCED BY EXCAVATION METHODS, MOISTURE, PRECIPITATION, GROUNDWATER CONTROL, AND CONSTRUCTION ACTIVITIES. THE CONTRACTOR SHALL TAKE PRECAUTIONS TO PREVENT SUBGRADE DISTURBANCE. SUCH PRECAUTIONS MAY INCLUDE DIVERTING STORMWATER RUNOFF AWAY FROM CONSTRUCTION AREAS, REDUCING TRAFFIC IN	R1-
	SENSITIVE AREAS, AND MAINTAINING AN EFFECTIVE DEWATERING PROGRAM. SOILS EXHIBITING HEAVING OR INSTABILITY SHALL BE OVER EXCAVATED TO MORE COMPETENT BEARING SOIL AND REPLACED WITH FREE DRAINING STRUCTURAL FILL MEETING THE ENGINEERS SPECIFIC RECOMMENDED CRITERIA.	R5-
3.)	IF THE EARTHWORK IS PERFORMED DURING FREEZING WEATHER (NOT ALLOWED IN TOWN R.O.W.), EXPOSED SUBGRADES ARE SUSCEPTIBLE TO FROST. NO FILL OR UTILITIES SHALL BE PLACED ON FROZEN GROUND. THIS WILL LIKELY REQUIRE REMOVAL OF A FROZEN SOIL CRUST AT THE	
	COMMENCEMENT OF EACH DAY'S OPERATION. THE FINAL SUBGRADE ELEVATION WOULD ALSO REQUIRE AN APPROPRIATE DEGREE OF INSULATION AGAINST FREEZING.	W11-
4.)	PLACEMENT OF BORROW MATERIALS SHALL BE PERFORMED IN A MANNER THAT PREVENTS LONG TERM DIFFERENTIAL SETTLEMENT. EXCESSIVELY WET MATERIALS SHALL BE STOCKPILED AND ALLOWED TO DRAIN BEFORE PLACEMENT. FROZEN MATERIAL SHALL NOT BE USED FOR CONSTRUCTION.	
5.)	FINAL UTILITY LOCATIONS TO BE COORDINATED BETWEEN THE CONTRACTOR, ALL APPROPRIATE UTILITY COMPANIES.	
6.)	ALL WATER MAIN AND SERVICE INSTALLATIONS SHALL CONFORM TO TOWN OF BARRINGTON STANDARDS. ALL HIGHWAY CONSTRUCTION WILL MEET THE TOWN OF BARRINGTON STANDARDS. (NOT APPLICABLE)	R7-6
7.)	CONTRACTOR SHALL COORDINATE ALL ELECTRICAL INSTALLATIONS WITH EVERSOURCE AT (800) 662–7764. ALL ELECTRIC CONDUIT INSTALLATION SHALL BE INSPECTED BY EVERSOURCE PRIOR TO BACKFILL. A 48–HOUR MINIMUM NOTICE IS REQUIRED.	R7–8
8.)	CONTRACTOR SHALL COORDINATE ALL TELECOMMUNICATIONS INSTALLATIONS WITH FAIRPOINT COMMUNICATIONS AT (603) 427-5525.	
9.)	THE APPLICANT IS ABLE TO MAKE LIKE CHANGES TO PRODUCTS SO LONG AS THE DESIGN ENGINEER APPROVES THAT THEY MEET THE DESIGN INTENT.	
10.)	CONTRACTOR SHALL COORDINATE ALL CABLE INSTALLATIONS WITH BREEZELINE.	
11.)	PROPANE TO BE PROVIDED VIA ABOVE GROUND TANKS LOCATED NO CLOSER THAN 10' TO ANY STRUCTURE.	

- 12.) VERTICAL DATUM BASED ON NAVD88 ELEVATIONS. HORIZONTAL DATUM BASED ON NAD83 STATE PLANE COORDINATES GATHERED USING CARLSON BRX7 SURVEY GRADE GPS.
- 13.) CONTRACTOR TO TRANSFER TEMPORARY BENCHMARK TO A SUITABLE BENCHMARK TO CONTROL CONSTRUCTION. ANY ELEVATION DISCREPANCIES ARE TO BE REPORTED TO THE THE DESIGN ENGINEER IMMEDIATELY.

SIGN ID NUMBER	SIGN SIZE (WIDTH × HEIGHT)	SIGN	TEXT DIMENSIONS	NO. OF SIGNS	BACKGROUND	LEGEND	BORDER	POST SIZE & QUANTITY
R1-1	30"×30"	STOP	SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT - FHWA	1	RED	WHITE	WHITE	SQUARE (1)
R5-1	30"×30"	DO NOT ENTER	SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT - FHWA	1	RED	WHITE	WHITE	U-CHANNEL (0)
W11-2	30"×30"		SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT - FHWA	3	YELLOW	BLACK	BLACK	SQUARE (3)
R7-8	12"x18"	RESERVED PARKING	SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT - FHWA	2	WHITE	GREEN W/ WHITE SYMBOL ON BLUE	GREEN	SQUARE (2)
R7-8a	12"x6"	VAN ACCESSIBLE	SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT – FHWA	1	WHITE	GREEN	GREEN	SQUARE (0)
	4"×4"	BIORETENTION SYSTEM		4	GREEN	WHITE	WHITE	U–CHANNEL (2)
	4"×4"	INFILTRATION SYSTEM		2	GREEN	WHITE	WHITE	U-CHANNEL (1)
W16-9P	24"x12"	AHEAD	SEE STANDARD HIGHWAY SIGNS 2004 EDITION PUBLISHED BY USDOT – FHWA	3	YELLOW	BLACK	BLACK	U–CHANNEL (3)

EROSION AND SEDIMENT CONTROL NOTES:

- 1.) EROSION AND SEDIMENT CONTROL INSPECTIONS TO BE CONDUCTED ONCE PER EVERY SEVEN DAYS AND AT AN INCREASED FREQUENCY INCLUDING WITHIN 24-HOURS OF A 0.25 INCH RAIN EVENT. INSPECTIONS TO BE CONDUCTED BY A "QUALIFIED PERSON" AS DEFINED BY EPA CGP 4.1.1 AND INSPECTION REPORTS SUBMITTED TO THE TOWN OF BARRINGTON, PLANNING DEPARTMENT WITHIN 24 HOURS IN ACCORDANCE WITH CGP 4.1.7 AND MAINTAINED BY THE OWNER FOR A PERIOD OF THREE YEARS AFTER THE PROJECT IS COMPLETED.
- 2.) PER EPA CGP Z.1.2.2 (INSTALL PERIMETER CONTROL), "YOU MUST INSTALL SEDIMENT CONTROLS ALONG THOSE PERIMETER AREAS OF YOUR SITE THAT WILL RECEIVE STORMWATER FROM EARTH DISTURBING ACTIVITIES." AS A RESULT OF SWPPP INSPECTIONS, THE CONTRACTOR MAY HAVE TO EXPAND PERIMETER CONTROLS TO MEET THIS REQUIREMENT. THE E&SC PLAN IS INITIAL GUIDANCE AS TO THE ANTICIPATED REQUIREMENTS AND IT IS THE CONTRACTORS RESPONSIBILITY TO ENSURE THAT STORMWATER VIOLATIONS DO NOT OCCUR
- 3.) CONTRACTOR IS REQUIRED TO HAVE A CONSTRUCTION ENTRANCE 3" ANGULAR STONE IS REQUIRED.
- 4.) CONTRACTOR IS RESPONSIBLE FOR SWEEPING THE DRIVEWAY TO ENSURE THAT NO SEDIMENT IS BEING TRACKED ONTO CALEF HIGHWAY.
- 5.) CONTRACTOR IS RESPONSIBLE FOR CLEANING AND MAINTAINING THE INLET PROTECTION ONCE INSTALLED.
- 6.) FUGITIVE DUST IS TO BE CONTROLLED THROUGHOUT THE CONSTRUCTION PROCESS IN ACCORDANCE WITH ENV-A 1000.
- 7.) CONTRACTOR IS TO MEET THE REQUIREMENTS SPECIFIED IN RSA 430:51-57 AND AGR 3800, RELATING TO INVASIVE SPECIES.
- 8.) CONTRACTOR IS RESPONSIBLE FOR PROTECTING THE WATER QUALITY FROM ANY RUNOFF DURING THE CONSTRUCTION PROCESS, IN ACCORDANCE WITH ENV-WQ 1507, IN ORDER TO PREVENT VIOLATIONS OF THE STORMWATER QUALITY STANDARDS.
- 9.) CONTRACTOR CAN USE SILT FENCE, SILT SOXX OR MULCH BERM FOR PERIMETER CONTROL. SPECIFIC PRACTICES MAY BE SPECIFIED, SEE PLAN. SILT FENCE OR SILT SOXX REQUIRED WHEN UPGRADIENT DISTURBED SOIL IS GREATER THAN 5%. MULCH BERM CAN BE USED WHEN THE UPGRADIENT DISTURBED SOIL IS 5% OR LESS.
- 10.) CONTRACTOR TO BE AWARE OF THE SOIL PROFILES AND ENSURE THAT PROPER EROSION PREVENTION AND SEDIMENT CONTROL MEASURES ARE TAKEN AT ALL TIMES. ANY DEWATERING REQUIREMENTS IN NEW HAMPSHIRE REQUIRE SPECIAL PROVISIONS IN CCORDANCE WITH THE "CLARIFICATION OF SECTION 9.1.2 (STATE OF NEW HAMPSHIRE CONDITIONS) AND OTHER NH SPECIFIC INFORMATION FOR THE U.S. EPA 2022 NPDES CONSTRUCTION GENERAL PERMIT (CGP)" DATED FEBRUARY 17, 2022 INCLUDED IN THE SWPPP.
- 11.) COVER MANAGEMENT DURING CONSTRUCTION FOR EXPOSED SOIL WILL INCLUDE HAY / STRAW APPLIED AT A RATE OF 2.0 TONS PER ACRE, TEMPORARY SEEDING OF ANNUAL RYE GRASS, AND PERMANENT SEEDING AT THE EARLIES OPPORTUNITY. SEE ADDITIONAL REQUIREMENT FOR STABILIZATION ON THE EROSION AND SEDIMENT CONTROL DETAIL SHEETS, E-101 AND E-102.
- 12.) THE CONSTRUCTION SCHEDULE WILL BE MANAGED SO THAT ALL STORMWATER STRUCTURES WILL BE BUILT AND STABILIZED PRIOR TO RECEIVING SURFACE WATER RUNOFF. CONTRACTOR TO BE RESPONSIBLE FOR ALL DIVERSIONS DURING CONSTRUCTION AND FOR INTERIM SEDIMENT AND EROSION CONTROL MEASURES.

General Plant Bed Maintenance:

one inch of mulch and do not place the mulch closer than 3" to the trunks or stems of woody plants.

Tree

- The first year watering during dry periods will be necessary. 3" Inches of mulch maybe used. The mulch should be kept 3 inches from the trunk. Fertilizing is not necessary for the first year. Fertilizing in subsequent years only when and if the foliage is looking. weak.
- Fertilization should occur prior to Mat 31* or after trees have dropped their leaves for the year. Prune dead wood once a year.
- Depending on the amount of compaction the bed area receives, deep root aeration may be needed over time Woody Shrubs


The first year watering during dry periods will be necessary.


- 3" inches of mulch maybe used. The mulch should be kept 3 inches from the stems.
- Fertilization should occur prior to Mat 31* or after shrubs have dropped their leaves or gone dormant for the


Prune dead wood once a year.

- Grasses - Grasses only need to be dipped back at the end of the growing season and all the clippings removed from the area.
- Do not over mulch. Too much mulch will prohibit the grass from developing into a strong clump. Perennials - All perennials need to be pruned back after the first or second hard frost. A two-step method; first dead head all
- growth and development Fertilizing perennials once in the spring with a low phosphate fertilizer will help the plants to get started in the
- spring.

www.terrainplanning.com









General Plant Maintenance Guide

All plant maintenance should be performed by a qualified horticulturalist or licensed arborist. Cleaning the dead material out of the planting bed in the fail helps keep litter from building up around the plants and in some cases killing the plants. Watering the first year during dry periods will help get the plants established. Mulching every year is not necessary. Raking the old mulch and turning it over is all that is needed. When necessary only install

Fertilizing is not necessary for the first year. Fertilizing in subsequent years only when and if the foliage is looking

the flower heads and let drop to the ground for re-seeding. Second cut the stems back to 3" above the ground and remove the stem and leaf litter and place in compost. Do not over much. Too much mulch will prohibit the


KENNETH BERRY


⁄805


╺═ᢕ═╝


311 kast hill road hopkinton nh 03229


T:603-491-2322






















Site Specific Soils Map 238 Lot 44							
<u>Slopes</u>	Hydrologic <u>Soil Group</u>						
В	Hinckley	А					
A,B,C,D,E	A,B,C,D,E Windsor						
В	Wareham	С					
А	A Udorthents (Smoothed)						
A,B,C,D,E	Deerfield	В					
A,C,D,E	Udorthents	В					
А	Walpole	С					
А	Endoaquents (Sandy or Gravelly)						
B = 3 - 8% C	= 8-15% D = 15-25% E = 25- 50%	F = 50% +					



TEST PIT DATA: DATE : 1/22/24 TEST PIT #207 0-4 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 4-16 7.5YR 5/6 STRONG BROWN, LOAMY SAND, GRANULAR, FRIABLE 16-30 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 30-40 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 40-65 2.5Y 6/3 LIGHT YELLOWISH BROWN, SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H*.*W.T. @ 40" RESTRICTIVE LAYER @ N/A ground water @ n/a" TERMINATED @ 65" REFUSAL @ N/A test pit #208 0-10 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 10–18 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 18-36 2.5Y 6/4 LIGHT YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 36-65 2.5YR 4/4 REDDISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 36" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A TERMINATED @ 65" REFUSAL © N/A test pit #209 0-10 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 10-18 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 18-34 2.5Y 6/4 LIGHT YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 34-65 2.5YR 4/4 REDDISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H*.*W.T. @ 34" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A TERMINATED @ 65" REFUSAL @ N/A TEST PIT #210 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-14 7.5YR 5/6 STRONG BROWN, LOAMY SAND, GRANULAR, FRIABLE 14-24 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 24-32 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 32-64 2.5Y 6/3 LIGHT YELLOWISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H*.*W.T. @ 32" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A TERMINATED @ 64" REFUSAL @ N/A TEST PIT #211 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8–14 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 14-22 10YR 6/4 LIGHT YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 22-60 2.5Y 6/3 LIGHT YELLOWISH BROWN, SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 22" RESTRICTIVE LAYER @ N/A ground water @ 32" TERMINATED @ 60" REFUSAL © N/A TEST PIT #212 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-16 7.5YR 5/6 STRONG BROWN, LOAMY SAND, GRANULAR, FRIABLE 16-28 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 26-38 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 38-60 2.5Y 6/3 LIGHT YELLOWISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 38" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A TERMINATED @ 60" REFUSAL @ N/A TEST PIT #213 0-10 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 10-24 10 YR 5/4 YELLOWISH BROWN, GRAVELLY SAND, SINGLE GRAIN, LOOSE 24-42 10YR 3/1 VERY DARK GRAY, LOAMY FINE SAND, MASSIVE, FRIABLE 42-52 2.5Y 6/3 LIGHT YELLOWISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H*.*W.T. @ 42" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A TERMINATED @ 52" REFUSAL @ N/A NOTE: 0-24" IS FILL MATERIAL. SOME CONCRETE IN FILL MATERIAL 10-24" TEST PIT #214 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-28 10YR 6/4 LIGHT YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 28-36 10YR 3/1 VERY DARK GRAY, LOAMY FINE SAND, GRANULAR, FRIABLE 36-50 2.5Y 6/3 LIGHT YELLOWISH BROWN, SAND AND FINE SAND WITH REDOX. FEAT. PRESENT, MASSIVE, FRIABLE E.S.H.W.T. @ 36" RESTRICTIVE LAYER @ N/A GROUND WATER @ N/A" TERMINATED @ 50" REFUSAL @ N/A

TEST PIT DATA: DATE : 3/7/24 TEST PIT #301 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-18 10YR 5/6 YELLOWISH BROWN, GRAVELLY LOAMY SAND, GRANULAR, FRIABLE 18-30 10YR 6/4 LIGHT YELLOWISH BROWN, GRAVELLY LOAMY SAND, GRANULAR, FRIABLE 30-44 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 44-52 2.5YR 5/3 LIGHT YELLOWISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 44" RESTRICTIVE LAYER @ N/A ground water @ n/a TERMINATED @ 52" REFUSAL @ N/A TEST PIT #302 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-18 10YR 5/6 YELLOWISH BROWN, GRAVELLY LOAMY SAND, GRANULAR, FRIABLE 18-32 10YR 6/4 LIGHT YELLOWISH BROWN, GRAVELLY LOAMY SAND, GRANULAR, FRIABLE 32-46 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 46-52 2.5YR 5/3 LIGHT YELLOWISH BROWN, GRAVELLY SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 46" RESTRICTIVE LAYER @ N/A ground water @ n/a TERMINATED © 52" REFUSAL @ N/A TEST PIT #303 0-8 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 8-14 7.5YR 5/6 STRONG BROWN, LOAMY SAND, GRANULAR, FRIABLE 14-26 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 26-32 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 32-52 2.5YR 6/3 LIGHT YELLOWISH BROWN, SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 32" RESTRICTIVE LAYER @ N/A ground water @ n/a TERMINATED @ 52" REFUSAL @ N/A TEST PIT #304 0-6 10YR 3/2 DARK GRAYISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 6–14 7.5YR 5/6 STRONG BROWN, LOAMY SAND, GRANULAR, FRIABLE 14-28 10YR 5/6 YELLOWISH BROWN, LOAMY SAND, GRANULAR, FRIABLE 28-42 10YR 6/4 LIGHT YELLOWISH BROWN, SAND, SINGLE GRAIN, LOOSE 42-52 2.5YR 6/3 LIGHT YELLOWISH BROWN, SAND WITH REDOX. FEAT. PRESENT, SINGLE GRAIN, LOOSE E.S.H.W.T. @ 42" RESTRICTIVE LAYER @ N/A ground water @ n/a TERMINATED @ 52"


REFUSAL @ N/A





		SION DATE DESCRIPTION
IESI PII DAIA	FOR TURBOCAM, INC. LAND OF VIRTUOUS REALTY, LLC NH ROUTE 125/CALEF HIGHWAY	BARRINGTON, N.H. TAX MAP 238, LOT 44 REVISIO
BFRRY SURVEYING		FILE NO. :


FOR PLANNING BOARD APPROVAL PURPOSES:


THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO.















































NOTES:

- 1A.) APPLICANT: TURBOCAM, INC.
- 2.) TAX MAP 238, LOT 44
- 3.) LOT AREA: 1,217,250 Sq.Ft., 27.94 Ac.
- 4.) S.C.R.D. BOOK 2948, PAGE 332

- STANDARDS.



DEERFIELD HINCKLEY


VIRTUOUS REALTY, LLC 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 INC. LOAMY SAND 313 K= 0.15 LOAMY SAND K= 0.17 WINDSOR LOAMY SAND K= 0.17 SEE WERSOIL LISDA-NR THE SWPPP. СD URVEYING ENGINEERING crown point road crown point road h 03825 (603)332-2 LEGEND: ONCRETE BOUND ~FND~ CATCH BASIN W/ STRUCTURE STORMWATER BMP OUTLET STRUCTURE ∩S S BENCHMARK (T.B.M.) EET / DETAIL 8 AINED JURISDICTIONAL WETLAND ND BUFFER З Ц С Ц С Ц С INOR, EXISTING MAJOR, EXISTING MINOR, PROPOSED 35 MAJOR, PROPOSED CENTER LINE \square EXISTING DRAINAGE LINE ш PROPOSED DRAINAGE LINE FOR TOWN APPROVAL PURPOSES : RIP RAP "OF NEW HA STORMWATER BEST MANAGEMENT PRACTICE (BMP) KENNETH BERM Α. BERRY SILT FENCE / EROSION MIX BERM No. 14243 FILTREXX 8" - 12" SILT SOXX AS SPECIFIED ORANGE CONSTRUCTION PERIMETER FENCE THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO. PERIMETER CONTROL STORMWATER BMP PROTECTION PERIMETER CONTROL RESIDENTIAL/ROADWAY CONSTRUCTION SHEET 27 OF 43

SOILS & DEWATERING: 12 26SEE SITE SPECIFIC SOILS MAP (SSSM) ERODIBILITY FACTOR - K, CPESC MANUAL, ENVIROCERT INTERNATIONAL INC. & CONTRACTOR TO BE AWARE OF THE SOIL PROFILES AND ENSURE THAT PROPER EROSION PREVENTION 9.1.2 (STATE OF NEW HAMPSHIRE CONDITIONS) AND OTHER NH SPECIFIC INFORMATION FOR THE U.S. EPA 2022 NPDES CONSTRUCTION GENERAL PÉRMIT (CGP)" DATED FEBRUARY 17, 2022 INCLUDED IN SEEDING AT THE EARLIES OPPORTUNITY. SEE ADDITIONAL REQUIREMENT FOR STABILIZATION ON THE EROSION AND SEDIMENT CONTROL DETAIL SHEETS, E-101 AND E-102. RESPONSIBLE FOR ALL DIVERSIONS DURING CONSTRUCTION AND FOR INTERIM SEDIMENT AND EROSION CONTROL MEASURES.

5.) EROSION AND SEDIMENT CONTROL INSPECTIONS TO BE CONDUCTED ONCE PER EVERY SEVEN DAYS AND AT AN INCREASED FREQUENCY INCLUDING WITHIN 24-HOURS OF A 0.25 INCH RAIN EVENT. INSPECTIONS TO BE CONDUCTED BY A "QUALIFIED PERSON" AS DEFINED BY EPA CGP 4.1.1 AND INSPECTION REPORTS SUBMITTED O THE TOWN OF BARRINGTON, LAND USE DEPARTMENT WITHIN 24 HOURS IN ACCORDANCE WITH CGP 4.1.7 AND MAINTAINED BY THE OWNER FOR A PERIOD OF THREE YEARS AFTER THE PROJECT IS COMPLETED. 6.) PER EPA CGP Z.1.2.2 (INSTALL PERIMETER CONTROL), "YOU MUST INSTALL SEDIMENT CONTROLS ALONG THOSE PERIMETER AREAS OF YOUR SITE THAT WILL RECEIVE STORMWATER FROM EARTH DISTURBING ACTIVITIES." AS A RESULT OF SWPPP INSPECTIONS, THE CONTRACTOR MAY HAVE TO EXPAND PERIMETER CONTROLS TO MEET THIS REQUIREMENT. THE E&SC PLAN IS INITIAL GUIDANCE AS TO THE ANTICIPATED REQUIREMENTS AND IT IS THE CONTRACTORS RESPONSIBILITY TO ENSURE THAT STORMWATER VIOLATIONS DO NOT OCCUR. 7.) CONTRACTOR IS REQUIRED TO HAVE A CONSTRUCTION ENTRANCE 3" ANGULAR STONE IS REQUIRED. 8.) CONTRACTOR IS RESPONSIBLE FOR SWEEPING THE DRIVEWAY TO ENSURE THAT NO SEDIMENT IS BEING TRACKED ONTO CALEF HIGHWAY OR THE REMAINDER OF THE EXISTING TURBOCAM SITE. 9.) CONTRACTOR IS RESPONSIBLE FOR CLEANING AND MAINTAINING THE INLET PROTECTION ONCE INSTALLED. 10.) FUGITIVE DUST IS TO BE CONTROLLED THROUGHOUT THE CONSTRUCTION PROCESS IN ACCORDANCE WITH ENV-A 1000. 11.) CONTRACTOR IS TO MEET THE REQUIREMENTS SPECIFIED IN RSA 430:51-57 AND AGR 3800, RELATING TO INVASIVE SPECIES. 12.) CONTRACTOR IS RESPONSIBLE FOR PROTECTING THE WATER QUALITY FROM ANY RUNOFF DURING THE CONSTRUCTION PROCESS, IN ACCORDANCE WITH ENV-WQ 1507, IN ORDER TO PREVENT VIOLATIONS OF THE STORMWATER QUALITY 13.) CONTRACTOR CAN USE SILT FENCE, SILT SOXX OR MULCH BERM FOR PERIMETER CONTROL. SPECIFIC PRACTICES MAY BE SPECIFIED, SEE PLAN. SILT FENCE OR SILT SOXX REQUIRED WHEN UPGRADIENT DISTURBED SOIL IS GREATER THAN 5%. MULCH BERM CAN BE USED WHEN THE UPGRADIENT DISTURBED SOIL IS 5% OR LESS. ROCKINGHAM COUNTY SOIL SURVEY, ROCKWEB SOIL ATTRIBUTES. AND SEDIMENT CONTROL MEASURES ARE TAKEN AT ALL TIMES. ANY DEWATERING REQUIREMENTS IN NEW HAMPSHIRE REQUIRE SPECIAL PROVISIONS IN ACCORDANCE WITH THE "CLARIFICATION OF SECTION COVER MANAGEMENT DURING CONSTRUCTION FOR EXPOSED SOIL WILL INCLUDE HAY / STRAW APPLIED AT A RATE OF 2.0 TONS PER ACRE, TEMPORARY SEEDING OF ANNUAL RYE GRASS, AND PERMANENT THE CONSTRUCTION SCHEDULE WILL BE MANAGED SO THAT ALL STORMWATER STRUCTURES WILL BE BUILT AND STABILIZED PRIOR TO RECEIVING SURFACE WATER RUNOFF. CONTRACTOR TO BE — F176 ——— D ··· _____ SF _____ — ss — ss — ss — — c — c — c — —— P/C——


- F175 -----


·	GRANITE/CO
	PROPOSED (
X	PROPOSED S
	TEMPORARY
E101 E6	DETAIL SHEE
	POORLY DRA 50' WETLANI CONTOUR MI CONTOUR MI CONTOUR MI CONTOUR MI



VIRTUOUS REALTY, LLC 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 NO LOAMY SAND K= 0.15 LOAMY SAND K= 0.17 K= 0.17 LOAMY SAND SURVEYING ENGINEERING CROWN POINT ROAD H 03825 (603)332-28 -''AI'S 40 FT. GRANITE/CONCRETE BOUND ~FND~ PROPOSED CATCH BASIN W/ STRUCTURE PROPOSED STORMWATER BMP OUTLET STRUCTURE TEMPORARY BENCHMARK (T.B.M.) ∩S S NHN DETAIL SHEET / DETAIL SND SND POORLY DRAINED JURISDICTIONAL WETLAND О́О 50' WETLAND BUFFER CONTOUR MINOR, EXISTING S C C C CONTOUR MAJOR, EXISTING CONTOUR MINOR, PROPOSED 35 71 CONTOUR MAJOR, PROPOSED CENTER LINE EXISTING DRAINAGE LINE \square DA PROPOSED DRAINAGE LINE ш FOR TOWN APPROVAL PURPOSES : OF NEW HAN STORMWATER BEST MANAGEMENT PRACTICE (BMP) KENNETH Α. BERRY SILT FENCE / EROSION MIX BERM FILTREXX 8" – 12" SILT SOXX AS SPECIFIED ORANGE CONSTRUCTION PERIMETER FENCE No. 14243 THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO. PERIMETER CONTROL STORMWATER BMP PROTECTION PERIMETER CONTROL RESIDENTIAL/ROADWAY CONSTRUCTION SHEET 28 OF 43

5.) EROSION AND SEDIMENT CONTROL INSPECTIONS TO BE CONDUCTED ONCE PER EVERY SEVEN DAYS AND AT AN INCREASED FREQUENCY INCLUDING WITHIN 24-HOURS OF A 0.25 INCH RAIN EVENT. INSPECTIONS TO BE CONDUCTED BY A "QUALIFIED PERSON" AS DEFINED BY EPA CGP 4.1.1 AND INSPECTION REPORTS SUBMITTED O THE TOWN OF BARRINGTON, LAND USE DEPARTMENT WITHIN 24 HOURS IN ACCORDANCE WITH CGP 4.1.7 AND MAINTAINED BY THE OWNER FOR A PERIOD OF THREE YEARS AFTER THE PROJECT IS COMPLETED. 6.) PER EPA CGP Z.1.2.2 (INSTALL PERIMETER CONTROL), "YOU MUST INSTALL SEDIMENT CONTROLS ALONG THOSE PERIMETER AREAS OF YOUR SITE THAT WILL RECEIVE STORMWATER FROM EARTH DISTURBING ACTIVITIES." AS A RESULT OF SWPPP INSPECTIONS, THE CONTRACTOR MAY HAVE TO EXPAND PERIMETER CONTROLS TO MEET THIS REQUIREMENT. THE E&SC PLAN IS INITIAL GUIDANCE AS TO THE ANTICIPATED REQUIREMENTS AND IT IS THE CONTRACTORS RESPONSIBILITY TO ENSURE THAT STORMWATER VIOLATIONS DO NOT OCCUR. 7.) CONTRACTOR IS REQUIRED TO HAVE A CONSTRUCTION ENTRANCE 3" ANGULAR STONE IS REQUIRED. CONTRACTOR IS RESPONSIBLE FOR SWEEPING THE DRIVEWAY TO ENSURE THAT NO SEDIMENT IS BEING TRACKED ONTO CALEF HIGHWAY OR THE REMAINDER OF THE EXISTING TURBOCAM SITE. 9.) CONTRACTOR IS RESPONSIBLE FOR CLEANING AND MAINTAINING THE INLET PROTECTION ONCE INSTALLED. 10.) FUGITIVE DUST IS TO BE CONTROLLED THROUGHOUT THE CONSTRUCTION PROCESS IN ACCORDANCE WITH ENV-A 1000. 11.) CONTRACTOR IS TO MEET THE REQUIREMENTS SPECIFIED IN RSA 430:51-57 AND AGR 3800, RELATING TO INVASIVE SPECIES. 12.) CONTRACTOR IS RESPONSIBLE FOR PROTECTING THE WATER QUALITY FROM ANY RUNOFF DURING THE CONSTRUCTION PROCESS, IN ACCORDANCE WITH ENV-WQ 1507, IN ORDER TO PREVENT VIOLATIONS OF THE STORMWATER QUALITY 13.) CONTRACTOR CAN USE SILT FENCE, SILT SOXX OR MULCH BERM FOR PERIMETER CONTROL. SPECIFIC PRACTICES MAY BE SPECIFIED, SEE PLAN. SILT FENCE OR SILT SOXX REQUIRED WHEN UPGRADIENT DISTURBED SOIL IS GREATER THAN 5%. MULCH BERM CAN BE USED WHEN THE UPGRADIENT DISTURBED SOIL IS 5% OR LESS. SEE SITE SPECIFIC SOILS MAP (SSSM) SEE WEBSOIL USDA-NRCS ERODIBILITY FACTOR - K, CPESC MANUAL, ENVIROCERT INTERNATIONAL INC. & ROCKINGHAM COUNTY SOIL SURVEY, ROCKWEB SOIL ATTRIBUTES. CONTRACTOR TO BE AWARE OF THE SOIL PROFILES AND ENSURE THAT PROPER EROSION PREVENTION AND SEDIMENT CONTROL MEASURES ARE TAKEN AT ALL TIMES. ANY DEWATERING REQUIREMENTS IN NEW HAMPSHIRE REQUIRE SPECIAL PROVISIONS IN ACCORDANCE WITH THE "CLARIFICATION OF SECTION 9.1.2 (STATE OF NEW HAMPSHIRE CONDITIONS) AND OTHER NH SPECIFIC INFORMATION FOR THE U.S. EPA 2022 NPDES CONSTRUCTION GENERAL PERMIT (CGP)" DATED FEBRUARY 17, 2022 INCLUDED IN COVER MANAGEMENT DURING CONSTRUCTION FOR EXPOSED SOIL WILL INCLUDE HAY / STRAW APPLIED AT A RATE OF 2.0 TONS PER ACRE, TEMPORARY SEEDING OF ANNUAL RYE GRASS, AND PERMANENT SEEDING AT THE EARLIES OPPORTUNITY. SEE ADDITIONAL REQUIREMENT FOR STABILIZATION ON THE EROSION AND SEDIMENT CONTROL DETAIL SHEETS, E-101 AND E-102. THE CONSTRUCTION SCHEDULE WILL BE MANAGED SO THAT ALL STORMWATER STRUCTURES WILL BE BUILT AND STABILIZED PRIOR TO RECEIVING SURFACE WATER RUNOFF. CONTRACTOR TO BE RESPONSIBLE FOR ALL DIVERSIONS DURING CONSTRUCTION AND FOR INTERIM SEDIMENT AND EROSION



















	VISION DATE DESCRIPTION
IS 0+00 - END	REV
FRONT TURBOCAM PARKING CROSS SECTIONS 0+00 - END	FOR TURBOCAM, INC. LAND OF VIRTUOUS REALTY, LLC NH ROUTE 125/CALEF HIGHWAY BARRINGTON, N.H. <i>TAX MAP 238, LOT 44</i>
RFRRY SURVEYING	335 SECONE 335 SECONE ARRINGTON, N CALE : 1 ATE : API LE NO. : DE
	NEW HAMS NEW HAMS KENNETH A. BERRY No. 14243 SHEET 29 OF 43








		DESCRIPTION	
		ON DATE	
		REVISION	
PARKING CROSS SECTIONS 10+00 - END	FOR TURBOCAM, INC. LAND OF VIRTUOUS REALTY, LLC NH ROUTE 125/CALEF HIGHWAY	TAX MAP 238, LOT 44	
RFRRY		DATE : APRIL 17, 2024	FILE NO . DB 2023 - 017
	HEET 30 OF	A HIM	
	JULLI JU UF		





I	design	specifications						
	Quantity	Manufacturer	Catalog Numb er	Description	Number Lamps	Lumens Per Lamp	Light Loss Factor	Wattage
	5	HADCO Independence	V15A-TS-N-D-150S -208V	V15A-TS-N-D-150S-208V	1	15,000		150

Statistics							
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min	
STAT ZONE #1	+	2 fc	3.6 fc	0.7 fc	5.1:1	2.9:1	
WAIVER REQUEST:							
SITE REVIEW R	EGULATI	ON ART			BLE #8: LS ABOVE		


	4" DSL (Y)		
HWAY	4" DSL (Y) 4" SSL (W)		
HU	or	004 004 004 004 004 004 004 004	
-UP EVERSOURCE 613/79Y-2 5 5 6 6 6 6 7 7 7 7 7 7 7 7 7 7 7 7 7	$\begin{array}{cccccccccccccccccccccccccccccccccccc$		
	$\begin{array}{c} \mathbf{x}_{0} \\ \mathbf{x}$	84 94 95 95 95 95 95 95 95 95 95 95 95 95 95	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{bmatrix} c_1 \\ c_2 \\ c_3 \\ c_4 \\ c_$		
$\frac{1}{2}$ $\frac{1}$	$\begin{array}{c} 1 \\ 1 \\ 2 \\ 2 \\ 3 \\ 4 \\ 4 \\ 3 \\ 4 \\ 4 \\ 4 \\ 3 \\ 4 \\ 4$	+	
$\begin{array}{c} +31\\ +31\\ +31\\ +31\\ +31\\ +31\\ +31\\ +31\\$	STAT ZONE #1 +2 +2 +2 +2 +2 +2 +2 +2 +2 +2 +2 +2 +2	ϕ_{1} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{4} ϕ_{2} ϕ_{4} ϕ_{2} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{2} ϕ_{3} ϕ_{4} ϕ_{2} ϕ	
$\begin{array}{c} \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ $	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \end{array} \\ \begin{array}{c} \\ \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \begin{array}{c} \\ \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ $	
0 1 1 1 1 1 1 1 1 1 1 1 1 1		+0 +0 +0 +0 +0 +0 +0 +0 +0 +0 +0 +0 +0 +	10 Marine
00+ 00+ 00+ 00+ 00+ 00+ 00+ 00+ 00+ 00+			
EXISTING POLE MOUNTED LIGHT MOUNTED 20' HIGH	© VIIIII	TAX MAP 238, LOT 44	
\$		1,217,250 Sq.Ft. 27.94 Ac. S.C.R.D. BOOK 2948, PAGE 332	
		EXISTING INDUSTRIAL BUILDING "TURBOCAM" 115,754 Sq.Ft.	
			 The max development is 2000 (2000)


Min :1 :E MEDIUM ACTIVITY LIGHTING LEVELS FOR A :SCRIBED: PENDING		z
		DESCRIPTION
<i>NOTES:</i> 1.) OWNER: VIRTUOUS REALTY, LLC 607 CALEF HIGHWAY, SUITE 200		DATE
1A.) APPLICANT: TURBOCAM INTERNATIONAL		
607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825		NISION
2.) TAX MAP 238, LOT 44 3.) LOT AREA: 1,217,250 Sq.Ft., 27.94 Ac.		REVI
4.) S.C.R.D. BOOK 2948, PAGE 332 5.) THE INTENT OF THIS PLAN IS TO SHOW THE EXISTING LIGHTING		
FOR THE PROPOSED PARKING AREA ON THE WEST SIDE OF A SITE PLAN PREPARED FOR TAX MAP 238, LOT 44. LECEND: GRANITE/CONCRETE BOUND ~FND~	LIGHTING PLAN WEST	FOR TURBOCAM, INC. LAND OF VIRTUOUS REALTY, LLC NH ROUTE 125/CALEF HIGHWAY BARRINGTON, N.H. <i>TAX MAP 238, LOT 44</i>
FOR PLANNING BOARD APPROVAL PURPOSES: THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO.	RERRY SURVEYING	ZIS SECON 335 SECON RRINGTON, N ALE : 1 ALE : API E NO. : DE


Schedule Symbol Label Image Quantity A	Manufacturer HADCO Independence INFORMATION USED FROM ORIGINAL SITE DESIGN	Catalog Number V15A–TS–N–D–150S –208V	Description V15A–TS–N–D–150	S-208V	Number Lamps 1	Lumens Per Lamp 15,000	Light Loss Factor	Wattage
B B B B B B B B B B B B B B B B B B B	Lithonia Lighting	DSX1 LED P1 30K T3M SOLAR	DSX1 LED P1 30K 1	13M SOLAR	1	6279	1	54
STAT ZONE #2 + 1.2 fc 2.4 fc 0.6 fc 4.0:1 2 STAT ZONE #3 + 1.1 fc 2.4 fc 0.4 fc 6.0:1 2 STAT ZONE #3 + 1.5 fc 2.4 fc 0.6 fc 4.0:1 2	g/Min .0:1 .0:1 .8:1 .5:1 .0:1							
WAIVER REQUEST: Site review regulation article 4.12.2 table #8: util Low activity use & average levels above pi	RESCRIBED: PEND	NG .	ELS FOR A	+0. ⁺	to.0 +	0.1	0.1	0.1
			+ +			++	_	+0.1
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0		FIELD to to to			+0.1	2		+0.2 +0.3
to.o to.o to.o to.o to.o		+0.0 +0.0 +0.0	+0.1	e +o.1	+++++++++++++++++++++++++++++++++++++++	·.4 +0 ·.7	4	3 +0.5 H
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0	0	0	MOUNTED :	H_0 +0	+00	++	to.9 +1.0	+0.8 +0.8
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0	+0.0 to.0	0 0		+0.2 +	+0.9	+	+	+++++++++++++++++++++++++++++++++++++++
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0	+0.0 +0.0 +0	0	+0.2 +0.3	+0.2 +0.2 +0.3 +0.3	·3 + ····	7 +1.8	+_ /	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	+0.0 +0.0 +0.0 +0.0	• • • • • • • • • • • • • • • • • • •	+0.1	+0.00	to the	8+1.8	+1.3	121.007+1214 +07
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0	+0.0	+0,1 +0,1	+0.2 +0.	±0.3 +0./ ±0.5	+1.4	+_1.7	+1.3	2 +1.0
+0.0 $+0.0$	0.0 + 0.0 + /	+0.1 +0.2 (+0.2 +0.2 +0.3	+0.00 +0.00 +0.00	+11	++	+0.8	+0.6
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0			+0.6 +0.7 +0.7	+0.6 +0.7 +1.1	+	+0	+0.6 +0	+0,4+0
+0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0 +0.0			+++++++++++++++++++++++++++++++++++++++	+_1 +_1 +_1 ····························	+1.3	Fo:8	+0	, 3 +0.3
	+0.1 +0.0 +0.0 +0.0		40. 12 +0. 12	+_1 +_1.8 +_1.0 +	++		$\langle \rangle$	0.4
			+0.2 +		+++	+1.6	+	
+0.0 +0.0 +0.0 +0.0	⁽ +0.0 +0.0 +0.0 +0.0	+0.1 +0.1 +0.1			+1.2 EE 91	400 +	+ 55,000	+0.6
+0. +0. +0. +0. +0. +0. +0. +0. +0. +0.		в — — — — — — — — — — — — — — — — — — —			+0.4		ⁱ	+0.8 0.8 +0.6 +
NADB3 NH STATE PLANE		**************************************	. +	⁵ - ¹ ¹ ¹ ¹ ¹ ¹ ¹	+0.2 +0.2	Ž, —	+0.7 +0.4	+0.5
MACNETIC		+<~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			ب			+0.3
				.0		+0.1	+0.1	+0.1 +0.1 +0.1 +0.1 +0.1 +0.1 +0.1 +0.1
LEGEND:			0.0 + 0.0 + 0.0	+0.0 +0.0	+0.0 +0.0	+0.0 +0.0		+0.0 +
GRANITE/CONCRETE BOUND ~FND~ REBAR ~FND~ UTILITY POLE C EXISTING LIGHT TYPE "A" MOUNTED ON POLE (D DROPOSED LIGHT TYPE "B" MOUNTED ON POLE (C D ROPOSED LIGHT TYPE "B" MOUNTED ON POLE (C D ROPOSED LIGHT TYPE "B" MOUNTED ON POLE (C D ROPOSED TYPE "B" MOUNTED TYPE "B" MOUNTED ON POLE (C D ROPOSED TYPE "B" MOUNTED TYPE "B" TYPE "	2 0'			+0.0	+0.0	+0.0	+0. , to ,	
-Ö PROPOSED LIGHT TYPE "B" MOUNTED ON POLE				+0.0	+0.0	\ † 0	+0.0	


+N TRM PK NALL SE PK NAIL SET ELEV. 191.77 +0 EXISTING PARKING + SMOKERS HUT 🛄 UNDER DRAIN (6" HDPE N-12) 6 IN STONE TRENCH +0 +4 +0 +0 õ . 0 EXISTING DECIDUOUS -TREE (TYP) 4 +0.2 +0.5 +0.3 +6 +____ +__ σ N TRANSFORMER ON CONCRETE PAD W/CONCRETE BOLLARDS 0.1 +_ EXISTING SNOW STORAGE N HO MAINTENANCE EXISTING GRAVEL AREA. PROPOSED PAVED AREA +0 +0 +0 ⁺0 - PROPOSED PAINTED PAVEMENT MARKING (TYP) 2 IR**6**N ~FND~ Ð + +0 +~ GRAPHIC SCALE (IN FEET) 1 inch = 20 ft. +0 +0.C ⁺<u>ọ</u> +<u>,</u> +<u>a</u> +_ +~ ċ / +

+0.1 +0.0 +0.0 +0.0	0.0 $+0.0$ $+$	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	DESCRIPTION
to.1 to.0 to.0 to.0 to.0 to.0 to.0 to.0 to.0	$+ \frac{1}{100} + $	REVISION DATE
$\begin{array}{c} + & + & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 \\ + & 0 & 0 & 0 & 0 \\ \end{array}$		LIGHTING PLAN – EAST FOR TURBOCAM, INC. LAND OF VIRTUOUS REALTY, LLC NH ROUTE 125/CALEF HIGHWAY BARRINGTON, N.H. <i>TAX MAP 238, LOT 44</i>
+ S.C.R.D. BOOK 5.) THE INTENT C FOR THE PRO	VIRTUOUS REALTY, LLC 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 TURBOCAM INTERNATIONAL 607 CALEF HIGHWAY, SUITE 200 BARRINGTON, NH 03825 3, LOT 44 217,250 Sq.Ft., 27.94 Ac. 3 (2948, PAGE 332 OF THIS PLAN IS TO SHOW THE EXISTING LIGHTING POSED PARKING AREA ON THE EAST SIDE OF A SITE YED FOR TAX MAP 238, LOT 44. FOR PLANNING BOARD APPROVAL PURPOSES: THE SITE REVIEW REGULATIONS OF THE TOWN OF BARRINGTON ARE A PART OF THIS PLAN, AND APPROVAL OF THIS PLAN IS CONTINGENT UPON COMPLETION OF ALL REQUIREMENTS OF SAID SITE REVIEW REGULATIONS, EXCEPTING ONLY MODIFICATIONS MADE IN WRITING BY THE BOARD AND ATTACHED HERETO.	BERRY SURVEYING BERRY SURVEYING BARRINGTON, NH 03825 (603)332-2863 SCALE : 1 IN. EQUALS 20 FT. DATE : APRIL 17, 2024 FILE NO. : DB 2023 - 017 FILE NO. : DB 2023 - 017














<i>E14</i>	TABLE 7-24RECOMM	ENDED RIP RAP GRADA	TION RANGES	_			
	d50 SIZE= 0.6	7 FEET 8	INCHES				
	% OF WEIGHT SMALLER THAN THE GIVEN 450 S	SIZE OF STON	E (INCHES) TO				
	100%	12	16				
	85%	10	14				
	50%	8	12			NO	
	15% d50 SIZE= 0.5	2 	4 INCHES			ШЦ	
	% OF WEIGHT SMALLER	SIZE OF STON	E (INCHES)			SCRIPTION	
	THAN THE GIVEN d50 S	SIZE FROM 9	12			DE	
	85%	8	11				
	50%	6	9				
	15%	2	3				
			<i>E17</i>				
OCATE ANY PROJ	JECT T.B.M. FION CONTROL FACILITIES AS S	PECIFIED FROSION AND SEDIN					
	PRIOR TO DIRECTING RUNOFF					ATE	
	AND STABILIZED EARLY IN TH		IUNS MAT BE			$\hat{\Box}$	
EEDED UNTIL SITE	IS STABILIZED.					Z	
E. TEMPORARY W	ATER DIVERSION (SWALES, ETG	C.) MUST BE USED AS NECESS	SARY UNTIL AREAS			ISION	
ALL ROADS SHALL	BE STABILIZED IMMEDIATELY.					RE <	
RED OR DIRECTED RADING.). INSTALL BIORETENTION W/ 1	SRS, INFILTRATION POND, AND	STORMTECH				
D WITHIN 45 DAY ES WILL BE CONS TELY IN ANY ARE DAYS. THE INSTAL	ND DISTURBED AREAS SHALL F 'S (ENV-WQ 1504.16) AND AB STRUCTED AND STABILIZED PRI AS OF EXPOSED SOIL WHERE LATION OF STABILIZATION WIL STABILIZED WITHIN 72 HOURS	UTTING PROPERTIES WILL NOT OR TO HAVING RUN-OFF DIRE CONSTRUCTION ACTIVITIES HAV _ BE COMPLETED AS SOON AS	BE ADVERSELY CTED TO THEM. /E PERMANENTLY S PRACTICABLE				
DURING CONSTRUC OFESSIONAL IN EF N STORM WATER	CH AND SEED AS REQUIRED. CTION. ALL SWPPP INSPECTION ROSION AND SEDIMENT CONTR QUALITY (CPSWQ). INSPECTION S OF A 0.25 INCH RAIN EVENT	DETAILS					
HAVE ESTABLISH	ED			DE	VAY		
OCCUR WITHIN				SOL). LLC HIGHWAY	44	
				CONTROI		L0T	
				\sim	ONLE OF	38,	
8 DEFI	INITION OF S	SEDIMENT	TURBOCAM, LAND OI TUOUS REAL TE 125/CAL 3ARRINGTON	х Д			
U		EDIV	URB UOU TE 1: ARRI	MA			
/-WQ 1500 AL	TERATION OF TERRAIN	হ	TU VIRTU ROUTE BAI	TAX			
/INIMUM OF 8	RAVELS HAVE BEEN INS 5 PERCENT VEGETATED	GROWTH HAS BEEN ES	TABLISHED		HN HN	Г	
-RAP HAS BE	INCHES OF NON-EROS			EROSION	2		
EROSION COI I STABILIZATIO	NTROL BLANKETS HAVE	BEEN PROPERLY INSTA	LLEU.	ER(
	OTHER APPROVED METH	ODS SHALL BE USED T	O CONTROL				
SION OF NEW		L CUT AND FILL SLOPE	ES SHALL BE				
BILIZED. IN A	AREAS SHALL BE EITHE REAS WHERE FINAL GRA	ADING HAS NOT OCCURI	RED,				
CALENDAR D	BILIZATION MEASURES S AYS FOR EXPOSED SOIL	. AREAS THAT ARE WIT	HIN ONE				
re than 14 (FEET OF A SURFACE WA CALENDAR DAYS FOR AI HOULD BE IN PLACE WIT	L OTHER AREAS, PERM	1ANEN T		20		
	PLETION OF FINAL GRAD				286		
					332-		
859 VECETAT	IVE COVERAGE PRIOR		D OO		3)33		
ulch at a ra	TE OF 3-4 TONS PER TO SWALES OR		E22			24	
E/PHOTODEGRA	ADABLE "JUTE MATTING" ILCHED AND TACKED AT					202	
s active afte	R JUTE MATTING SHALL R OCTOBER 15TH, ANY	<u>WINTER</u>			CLINC ROWN 03825 01ED	~ m	י
BE REMOVED, VE.	PRIOR TO SPRING	<u>STABILIZAT</u> NOTES	TON				
	HALL BE EITHER LINED			い え	이 수 이	APRIL DB 2	ו
S OR RIPRAP	WINTER MONTHS. IF WITH ENGINEERING				SECO, GTON,	< .	
UIDOWN OR A	S SOON AS THEY ARE			Ŕ	SE(
	BROUGHT UP TO AND VATIONS ARE PROPOSED	FOR TOWN APPROVAL	PURPOSES :		335 335 ARRIN(CALE:		
EL SHALL BE F				Ш	335 BARRI SCALE:	DATE FII F	
ONFORM TO NH	WILL REDUCE ROADWAY 1 DOT 304.3, BUT GEST STONE SIZE					, ,	
	JMULATED SNOW SHALL				NUMULAN OF NEW HAND		
AVERAGE GR	OWING SEASON, NO	THE SITE REVIEW REGULATION BARRINGTON ARE A PART OF APPROVAL OF THIS PLAN IS	S OF THE TOWN OF THIS PLAN, AND CONTINGENT UPON		NEW HAND	HIRE -	
ND SWALES. T DED BY THIS D	HE STOCKPILES THAT DATE, AFTER OCTOBER	COMPLETION OF ALL REQUIRE SITE REVIEW REGULATIONS, EX MODIFICATIONS MADE IN WRIT		- PRO	BERRY No. 14243		
	OF 3—4 TONS PER Shall be surrounded	AND ATTACHED HERETO.			TS CENSES ON AL	MMMM S	
	ARE OF EXPOSURE TO	F_	102				┛┃
waiver and w	INTER CONSTRUCTION		~	SHEET	36 OF 43		

















AMERICAN BUMBLE BEE

IDENTIFICATION/DESCRIPTION:

BOMBUS PENSYLVANICUS IS A LARGE BUMBLE BEE WITH THE QUEEN MEASURING 1 IN, THE WORKER FROM 0.5 IN, AND THE MALE FROM 0.75 IN IN LENGTH. THE QUEEN IS MOSTLY BLACK, INCLUDING THE LEGS, SPURS AND TEGULAE (BASE OF WING). TERGITE 1, OR THE MOST ANTERIOR BACK PORTION OF THE QUEEN IS OFTEN YELLOW ESPECIALLY IN THE MIDDLE. WORKER BEES' MIDDLE TERGITES ARE YELLOW, THE TAIL BLACK, AND FACE LONG, THEIR CHEEKS ARE SLIGHTLY LONGER THAN BROAD, AND THE CLYPEUS (NOSE) HAS LARGE PUNCTURES EXCEPT ON THE MID LINE. THE HAIR ON THE TOP OF THE HEAD IS BLACK, SHORT AND EVEN. MALES HAVE A YELLOW ABDOMEN WITH A BLACK HEAD AND BLACK STRIPING IN THE LOWER THORAX.



SPOTTED TURTLE IDENTIFICATION/DESCRIPTION: A SMALL 3–5 INCH TURTLE RECOGNIZED BY NUMEROUS YELLOW SPOTS COVERING A DARK CARAPACE. THE NUMBER OF SPOTS IS VARIABLE. SPOTS CAN ALSO BE FOUND ON THE HEAD AND LIMBS.



LITTLE BROWN BAT

IDENTIFICATION/DESCRIPTION:

THE LITTLE BROWN BAT IS A SMALL MAMMAL WITH A BODY LENGTH OF 2 1/2 - 4"AND WEIGHING APPROXIMATELY 1/8 TO 1/2 AN OUNCE. THE WINGSPAN OF LITTLE BROWN BATS RANGE FROM 9 - 11". BATS ARE THE ONLY MAMMALS THAT ENGAGE IN TRULY ACTIVE FLIGHT. AS THEIR NAME SUGGESTS THEY ARE GLOSSY BROWN ABOVE WITH A LIGHTER GRAY COLOR BELOW. THESE BATS CAN LIVE 20 TO 30 YEARS.



TRI-COLORED BAT

IDENTIFICATION/DESCRIPTION:

THE TRICOLORED BAT, FORMERLY KNOWN AS THE EASTERN PIPISTRELLE (PIPISTRELLUS SUBFLAVUS), IS A SMALL BAT WEIGHING 0.2 TO 0.3 OUNCES (5 TO 8 GR) AND HAS A WINGSPAN OF 8 TO 10 INCHES. THE TERM "TRICOLORED" REFERS TO THE BAT'S YELLOWISHBROWN COAT THAT IS DARK AT THE BASE, YELLOWISH-BROWN IN THE MIDDLE, AND DARK AT THE TIPS. THE WING MEMBRANES ARE BLACKISH, BUT THE FACE AND EARS HAVE A PINKISH COLOR. AN OBVIOUS IDENTIFYING CHARACTERISTIC OF THIS SPECIES IS THE PINK COLOR OF THE SKIN ON THE RADIUS BONE. THE FEET ARE ALSO RELATIVELY LARGE COMPARED TO ITS BODY SIZE.



NORTHERN LONG-EARED BAT IDENTIFICATION / DESCRIPTION:

THE NORTHERN LONG-EARED BAT IS A MEDIUM-SIZED BAT WITH A BODY LENGTH OF 3 TO 3.7 INCHES BUT A WINGSPAN OF 9 TO 10 INCHES. THEIR FUR COLOR CAN BE MEDIUM TO DARK BROWN ON THE BACK AND TAWNY TO PALE-BROWN ON THE UNDERSIDE. AS ITS NAME SUGGESTS, THIS BAT IS DISTINGUISHED BY ITS LONG EARS, PARTICULARLY AS COMPARED TO OTHER BATS IN ITS GENUS, MYOTIS



EASTERN SMALL-FOOTED BAT

IDENTIFICATION/DESCRIPTION:

THE EASTERN SMALL-FOOTED BAT HAS BROWNISH FUR, OFTEN WITH A GOLDEN SHEEN, THAT CONTRASTS WITH ITS BLACKISH FACE AND EARS, AND BLACKISH-BROWN WINGS AND TAIL MEMBRANE. IT CAN BE DISTINGUISHED FROM OTHER MYOTIS SPECIES BY ITS BLACK MASK AND SMALL SIZE. THE BODY IS LITTLE MORE THAN 3½ INCHES LONG, INCLUDING A 1½-INCH TAIL. ITS SMALL FEET, WHICH PROVIDE THE COMMON NAME, ARE LESS THAN A HALF-INCH AND ITS WINGSPAN RANGES FROM 81/4 TO 93/4 INCHES. THIS SPECIES FLIES SLOWLY AND ERRATICALLY, USUALLY ABOUT ONE TO THREE YARDS ABOVE THE GROUND.



